

VB6, VB7, VBC6, VBC7 3-pole mini reversing contactors

AC or DC operated with screw terminals – 4 to 5.5 kW



VB6-30-01



VB7-30-10





VBC6-30-10



VBC7-30-10

3-pole mini reversing contactors with screw terminals

IEC Rated	Rated control voltage UC		Auxiliary contacts fitted		Factory code	Order code	
Power 400 V AC-3	Current $\theta \leq 40^\circ\text{C}$ AC-1	50 Hz					
kW	A	V AC	V DC				
4	16	24		1	0	GJL1211901R0101	VB6301001
		24		0	1	GJL1211901R0011	VB6300101
		220 ... 240		1	0	GJL1211901R8100	VB6301080
		220 ... 240		0	1	GJL1211901R8010	VB6300180
5.5	20	24		1	0	GJL1311901R0101	VB7301001
		24		0	1	GJL1311901R0011	VB7300101
		220 ... 240		1	0	GJL1311901R8100	VB7301080
		220 ... 240		0	1	GJL1311901R8010	VB7300180
4	16		24	1	0	GJL1213901R0101	VBC6301001
			24	0	1	GJL1213901R0011	VBC6300101
5.5	20		24	1	0	GJL1313901R0101	VBC7301001
			24	0	1	GJL1313901R0011	VBC7300101

Other coil voltages and auxiliary contact arrangements available.
For more detailed product information, please refer to the Technical Catalogue: 1SBC100192C0206