



## ÖLFLEX® CRANE CF

Weather-resistant flat rubber cables with copper screening



**Info**

- For outdoor cable trolley application
- EMC-compliant

### Benefits

- Weather-resistant for harsh environmental conditions
- Flat cables need less space than round cables
- Smaller bending radii is possible
- Copper braiding screens the cable against electromagnetic interference

### Application range

- In crane systems on building sites and shipyards for fixed installation, or for flexible use in cable trolley systems
- Sewage treatment plants, steelworks and high rack facilities
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3
- As a lift control cable: max. 50 m suspension length

### Product features

- Flame-retardant according IEC 60332-1-2

### Norm references / Approvals

- Based on VDE 0250-809 (NGFLGÖU)

### Product Make-up

- Strands of bare or tinned-copper wires
- Core insulation: rubber compound
- Individual core screening consist of
  - plastic foil wrapping
  - tin-plated copper braiding
  - plastic foil wrapping
- Outer sheath: special rubber compound

### Technical data

**Classification ETIM 5/6**  
 ETIM 5.0/6.0 Class-ID: EC000825  
 ETIM 5.0/6.0 Class-Description: Flat cable

**Core identification code**  
 Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9  
 From 6 cores: black with white numbers

**Conductor stranding**  
 Copper conductor according to VDE 0295/IEC 60228  
 up to 25 mm<sup>2</sup>: extra-fine wire, class 6  
 from 35 mm<sup>2</sup>: fine wire, class 5

**Minimum bending radius**  
 Flexible use: 10 x cable thickness  
 Fixed installation: 4 x cable thickness

**Nominal voltage**  
 U0/U: 300/500 V

**Test voltage**  
 2000 V

**Protective conductor**  
 G = with GN-YE protective conductor  
 X = without protective conductor

**Temperature range**  
 Flexible use: -25°C to +90°C  
 Fixed installation: -40°C to +90°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer dimensions, width x height (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® CRANE CF</b>				
0041075	4 G 1,5	18,5 x 6,5	79	220
0041076	8 G 1,5	36,0 x 7,5	155	470
0041077	12 G 1,5	54,5 x 8,5	238	745
0041078	4 G 2,5	22,5 x 7,5	141	320
0041079	12 G 2,5	69,5 x 9,5	499	1180
0041080	4 G 4	29,0 x 10,5	219	505
0041081	4 G 6	31,0 x 10,5	302	605
0041082	4 G 10	36,0 x 11,5	472	840
0041083	4 G 16	41,5 x 13,5	687	1180
0041084	4 G 25	47,0 x 15,0	1114	1605
0041085	4 G 35	55,0 x 17,0	1482	2520
0041086	4 G 50	66,0 x 20,5	2238	3000

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
 Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
 Photographs and graphics are not to scale and do not represent detailed images of the respective products.

### Similar products

- ÖLFLEX® CRANE F refer to page 176
- ÖLFLEX® LIFT F refer to page 178

### Accessories

- Cable trolley systems
- Flat cable wedge clamps