



**H07V-K <HAR>**

European <HAR> cable type certification

**Info**

- CPR: Article number choice under [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)
- <HAR>



**Benefits**

- Cables' <HAR>marking also stands for the international endorsement of national certification institutes' testing marks and certificates, e. g. <VDE><HAR>. The <HAR>marking is of special importance in case of goods traffic between European countries.

**Application range**

- Laying in tubes, exposed or buried in plaster, and in closed installation ducts
- For direct laying on racks, troughs and tubes only as potential equalisation conductor

**Product features**

- Flame-retardant according IEC 60332-1-2
- Spool: d1 = 18 mm; d2 = 200 mm; b = 85 mm

**Norm references / Approvals**

- <HAR> cable type certification acc. EN 50525-2-31
- No cable type certified core insulation colours according to EN 50525-1/ VDE 0285-525-1: transparent, green (single colour), yellow (single colour), all double colours (except of green-yellow and yellow-green)

**Product Make-up**

- Fine-wired copper conductor of bare copper strands in line with conductor class 5 acc. IEC 60228
- Core insulation: Based on PVC

**Technical data**

- Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000993  
ETIM 5.0/6.0 Class-Description: Single core cable
- Conductor stranding**  
Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
- Minimum bending radius**  
According to EN 50565-1  
OD ≤ 8 mm: 4 x OD\* / 2 x OD\*\*;  
8 < OD ≤ 12 mm: 5 x OD\* / 3 x OD\*\*;  
OD > 12 mm: 6 x OD\* / 4 x OD\*\*
- Nominal voltage**  
U0/U: 450/750 V
- Test voltage**  
2500 V
- Current rating**  
VDE 0298 Part 4  
EN 50565-1/ VDE 0298-565-1
- Temperature range**  
Fixed installation: -40°C to +80°C  
Moved: +5°C to +70°C

Conductor cross-section (mm²)	Outer diameter [mm]	m/ring	m/spool	Copper index (kg/km)	Weight (kg/km)	brown	black	grey	blue	green/yellow
1.5	2.8 - 3.4		150	14.4	22	4520031S	4520011S	4520061S	4520021S	4520001S
2.5	3.4 - 4.1		100	24	37	4520032S	4520012S	4520062S	4520022S	4520002S
1.5	2.8 - 3.4	100		14.4	22	4520031	4520011	4520061	4520021	4520001
2.5	3.4 - 4.1	100		24	37	4520032	4520012	4520062	4520022	4520002
4	3.9 - 4.8	100		38.4	45	4520033	4520013	4520063	4520023	4520003
6	4.4 - 5.3	100		57.6	71	4520034	4520014	4520064	4520024	4520004
10	5.7 - 6.8	100		96	120	4520035	4520015	4520065	4520025	4520005
16	6.7 - 8.1			153.6	187	4520036	4520016	4520066	4520026	4520006
25	8.4 - 10.2			240	290	4521031	4521011		4521021	4521001
35	9.7 - 11.7			336	399	4521032	4521012	4521062	4521022	4521002
50	11.5 - 13.9			480	559		4521013		4521023	4521003
70	13.2 - 16			672	776		4521014		4521024	4521004
95	15.1 - 18.2			912	1031		4521015		4521025	4521005
120	16.7 - 20.2			1152	1285		4521016			4521006
150	18.6 - 22.5			1440	1563		4521017			4521007
185	20.6 - 24.9			1776	1915		4521018			4521008
240	23.5 - 28.4			2304	2550		4521019			4521009

Conductor cross-section (mm²)	Outer diameter [mm]	m/ring	m/spool	Copper index (kg/km)	Weight (kg/km)	orange	dark blue	white	green	yellow
1.5	2.8 - 3.4		150	14.4	22		4520141S	4520051S		
2.5	3.4 - 4.1		100	24	37		4520142S	4520052S		
1.5	2.8 - 3.4	100		14.4	22	4520091	4520141	4520051	4520121	4520111
2.5	3.4 - 4.1	100		24	37	4520092	4520142	4520052	4520122	4520112
4	3.9 - 4.8	100		38.4	45	4520093	4520143	4520053	4520123	4520113
6	4.4 - 5.3	100		57.6	71	4520094	4520144	4520054	4520124	4520114
10	5.7 - 6.8	100		96	120	4520095	4520145	4520055		
16	6.7 - 8.1			153.6	187	4520096	4520146	4520056	4520126	
25	8.4 - 10.2			240	290	4521091				
35	9.7 - 11.7			336	399	4521092				

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/spool	Copper index (kg/km)	Weight (kg/km)	violet	red	ultra-marine blue
1.5	2.8 - 3.4		150	14.4	22		4520041S	
2.5	3.4 - 4.1		100	24	37		4520042S	
1.5	2.8 - 3.4	100		14.4	22	4520071	4520041	4520161
2.5	3.4 - 4.1	100		24	37	4520072	4520042	4520162
4	3.9 - 4.8	100		38.4	45		4520043	4520163
6	4.4 - 5.3	100		57.6	71	4520074	4520044	4520164
10	5.7 - 6.8	100		96	120		4520045	
16	6.7 - 8.1			153.6	187		4520046	
25	8.4 - 10.2			240	290		4521041	
35	9.7 - 11.7			336	399		4521042	
50	11.5 - 13.9			480	559		4521043	
70	13.2 - 16			672	776		4521044	

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Packaging size: Coil ≤ 30 kg, otherwise drum

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

\*for conventional use, \*\*for careful bending; „OD“ = outer diameter

**Similar products**

- MULTI-STANDARD SC 2.1 refer to page 218
- MULTI-STANDARD SC 2.2 refer to page 221

**Accessories**

- Mobile crimp tool crimping pliers refer to page 1017
- DIN-assorted boxes conductor end sleeves refer to page 995
- PEW 8.87 crimping pliers refer to page 1000
- FLEXIMARK® Collar Snap-on refer to page 960

ÖLFLEX®  
UNITRONIC®  
ETHERLINE®  
HITRONIC®  
EPIC®  
SKINTOP®  
SILVYN®  
FLEXIMARK®  
ACCESSORIES  
APPENDIX