



MULTI-STANDARD SC 2.2

UL-listed (MTW), CSA (TEW), <HAR> H07V2-K: max. +90°C, UL (AWM): Umax = 1 kV, tinned-copper strands

Info

- Higher maximum conductor temperature - H07V2-K: +90 °C according to EN 50525-2-31
- Higher voltage range according to UL



Benefits

- For use in the most important global markets
- Reduction in technical documentation
- Easier storage; increases the cost-effectiveness of the production process
- Works with „Conductor end sleeves XL, insulated“

Application range

- Factory wiring
- Field wiring
- Frequency converter power supply
- Internal wiring of devices and in control cabinets
- Protected installation in and on lighting equipments

Product features

- Flame-retardant according IEC 60332-1-2
- Flame-retardant according to UL VW1/ CSA FT1
- Oil-resistant

Norm references / Approvals

- Multi-standard cables have conductor strands with nominal sizes in mm² or AWG/kcmil. The master size is mentioned in the table below, while the equivalent size of the other system can be found in the Appendix T16 of this catalogue. For this related secondary size the cross-section of the conductor mostly works out to be greater than the specified nominal value.
- Cable type certifications: <HAR> H07V2-K acc. EN 50525-2-31, UL AWM style 10269 (by UL acc. UL standard UL 758, U.I. Lapp GmbH's UL AWM file number: E63634), (UL) MTW (by UL acc. UL standard UL 1063, U.I. Lapp GmbH's (UL) MTW file number: E198296), CSA TEW (by CSA acc. CSA standard CSA C22.2 No. 127, CSA class 5835-01)

Product Make-up

- Fine-wire strand made of tinned-copper wires
- Special PVC-based core insulation

Technical data

- Classification ETIM 5/6**
ETIM 5.0/6.0 Class-ID: EC000993
ETIM 5.0/6.0 Class-Description: Single core cable
- Conductor stranding**
Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
- Minimum bending radius**
OD ≤ 8 mm: 4 x OD* / 2 x OD**;
8 < OD ≤ 12 mm: 5 x OD* / 3 x OD**;
OD > 12 mm: 6 x OD* / 4 x OD**
- Nominal voltage**
HAR / IEC: U0/U: 450/750 V;
UL (AWM): U: 1000 V;
UL (MTW): U: 600 V;
CSA (TEW): U: 600 V
- Temperature range**
Fixed installation:
HAR/IEC: -40°C to +90°C;
UL (AWM): -40°C to +105°C;
UL (MTW): -40°C to +90°C;
CSA (TEW): up to +105°C

Conductor cross-section (mm ²)	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	brown	black	grey
0.5	2.7	100		4.8	10	4150103	4150101	
0.75	2.9	100		7.2	13	4150201	4150201	
1	3.1	100		9.6	16	4150303	4150301	
1	3.1		2000	9.6	16		4150301K	
1.5	3.4	100		14.4	22	4150403	4150401	4150406
2.5	4	100		24	37	4150503	4150501	4150506
2.5	4		900	24	37		4150501K	
4	4.6	100		38.4	49	4150603	4150601	
4	4.6		600	38.4	49		4150601K	
6	5.1	100		57.6	71		4150701	4150706
10	6.8	100		96	120		4150801	
16	9	100		153.6	185		4150901	
25	10.2	100		240	260		4151001	
35	11.7			336	360		4151101	
50	13.9			480	535		4151201	
70	16			672	735		4151301	
95	18.2			912	930		4151401	

Conductor cross-section (mm ²)	Outer diameter [mm]	m/ring	Copper index (kg/km)	Weight (kg/km)	blue	green/yellow	orange
0.5	2.7	100	4.8	10	4150102		
0.75	2.9	100	7.2	13	4150202		
1	3.1	100	9.6	16	4150302	4150300	4150309
1.5	3.4	100	14.4	22	4150402	4150400	4150409
2.5	4	100	24	37	4150502	4150500	4150509
4	4.6	100	38.4	49	4150602	4150600	
6	5.1	100	57.6	71	4150702	4150700	
10	6.8	100	96	120	4150802	4150800	
16	9	100	153.6	185		4150900	
25	10.2	100	240	260		4151000	
35	11.7		336	360		4151100	

Conductor cross-section (mm ²)	Outer diameter [mm]	m/ring	Copper index (kg/km)	Weight (kg/km)	dark blue	white	yellow
0.5	2.7	100	4.8	10	4150114	4150105	
0.75	2.9	100	7.2	13	4150214	4150205	
1	3.1	100	9.6	16		4150305	
1.5	3.4	100	14.4	22	4150414	4150405	4150410
4	4.6	100	38.4	49	4150614	4150605	4150610

Conductor cross-section (mm ²)	Outer diameter [mm]	m/ring	Copper index (kg/km)	Weight (kg/km)	red
0.5	2.7	100	4.8	10	4150104
0.75	2.9	100	7.2	13	4150204
1	3.1	100	9.6	16	4150304
1.5	3.4	100	14.4	22	4150404
2.5	4	100	24	37	4150504
4	4.6	100	38.4	49	4150604
6	5.1	100	57.6	71	4150704

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Packaging size: Coil ≤ 30 kg, otherwise drum

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Non-harmonised, nominal cross-sections: 0.5 mm², 0.75 mm², 1 mm², 16 mm², 50 mm², 70 mm², 95 mm², 120 mm²

*for conventional use, **for careful bending; „OD“ = outer diameter

The outer diameters stated in the part number table are maximum values.

Similar products

- MULTI-STANDARD SC 2.1 refer to page 218

Accessories

- DIN-assorted boxes conductor end sleeves refer to page 995
- Conductor end sleeves XL, insulated refer to page 996
- EASY STRIP stripping and cutting tool refer to page 988
- PEW 8.87 crimping pliers refer to page 1000
- FLEXIMARK® Collar Snap-on refer to page 960

ÖLFLEX®
 UNITRONIC®
 ETHERLINE®
 HITRONIC®
 EPIC®
 SKINTOP®
 SILVYN®
 FLEXIMARK®
 ACCESSORIES
 APPENDIX