



## H07Z-K 90°C

Harmonised; halogen-free to protect human life, the environment and material assets



**Info**

- CPR: Article number choice under [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)
- Halogen-free and harmonised (HAR)
- For expanded ambient temperatures and higher conductor cross-sections see ÖLFLEX® HEAT 125 SC

### Benefits

- Protection of human life and the environment thanks to the avoidance of the formation of acid in case of fire
- Time-saving assembly

### Application range

- For wiring of lamps, devices, switchgear cabinets and distribution boxes
- For installation in tubes, on, in and under plaster as well as in closed installation ducts
- In building with a high density of people or valuable assets
- For use in dry rooms
- For expanded ambient temperatures and higher conductor cross-sections see ÖLFLEX® HEAT 125 SC

### Product features

- The insulation material is halogen-free and free of other materials which could release toxic gases in the event of fire
- Low amount of corrosive gases in the event of fire
- Low smokes/low smoke density in the event of fire according to IEC 61034
- Flame-retardant according to IEC 60332-1-2

### Norm references / Approvals

- <HAR> cable type certification acc. EN 50525-3-41
- No cable type certified core insulation colours according to EN 50525-1/ VDE 0285-525-1: transparent, green (single colour), yellow (single colour), all double colours (except of green-yellow and yellow-green)

### Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Halogen-free

### Technical data

**Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000993  
ETIM 5.0/6.0 Class-Description: Single core cable

**Conductor stranding**  
Fine wire according to VDE 0295  
Class 5/ IEC 60228 Class 5

**Minimum bending radius**  
According to EN 50565-1  
OD ≤ 8 mm: 4 x OD\* / 2 x OD\*\*;  
8 < OD ≤ 12 mm: 5 x OD\* / 3 x OD\*\*;  
OD > 12 mm: 6 x OD\* / 4 x OD\*\*

**Nominal voltage**  
U0/U: 450/ 750 V

**Test voltage**  
2500 V

**Current rating**  
VDE 0298-4  
EN 50565-1/ VDE 0298-565-1

**Temperature range**  
During installation: -5°C up to +90°C  
Fixed installation: -40°C up to +90°C

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	brown	black	grey	blue
1.5	2.8 - 3.5	100		14.4	20	4726031	4726011	4726061	4726021
1.5	2.8 - 3.5		1500	14.4	20	4726031K	4726011K	4726061K	4726021K
2.5	3.4 - 4.3	100		24	32	4726032	4726012	4726062	4726022
2.5	3.4 - 4.3		900	24	32	4726032K	4726012K	4726062K	4726022K
4	3.9 - 4.9	100		38.4	45	4726033	4726013	4726063	4726023
4	3.9 - 4.9		600	38.4	45	4726033K	4726013K	4726063K	4726023K
6	4.4 - 5.5	100		57.6	65	4726034	4726014	4726064	4726024
6	4.4 - 5.5		400	57.6	65	4726034K	4726014K	4726064K	4726024K
10	5.7 - 7.1	100		96	110	4726035	4726015	4726065	4726025
16	6.7 - 8.4	100		153.6	170	4726036	4726016	4726066	4726026
25	8.4 - 10.6	100		240	290	4726037	4726017	4726067	4726027
35	9.7 - 12.1			336	380	4726038	4726018	4726068	4726028
50	11.5 - 14.4			480	530	4726039	4726019	4726069	4726029
70	13.2 - 16.6			672	750	4727031	4727011	4727061	4727021
95	15.1 - 18.8			912	1000	4727032	4727012	4727062	4727022

ÖLFLEX®  
 UNITRONIC®  
 ETHERLINE®  
 HITRONIC®  
 EPIC®  
 SKINTOP®  
 SILVYN®  
 FLEXIMARK®  
 ACCESSORIES  
 APPENDIX

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	green/yellow	orange	dark blue	white
1.5	2.8 - 3.5	100		14.4	20	4726001	4726091	4726141	4726051
1.5	2.8 - 3.5		1500	14.4	20	4726001K	4726091K	4726141K	4726051K
2.5	3.4 - 4.3	100		24	32	4726002	4726092	4726142	4726052
2.5	3.4 - 4.3		900	24	32	4726002K	4726092K	4726142K	4726052K
4	3.9 - 4.9	100		38.4	45	4726003	4726093	4726143	4726053
4	3.9 - 4.9		600	38.4	45	4726003K	4726093K	4726143K	4726053K
6	4.4 - 5.5	100		57.6	65	4726004	4726094	4726144	4726054
6	4.4 - 5.5		400	57.6	65	4726004K	4726094K	4726144K	4726054K
10	5.7 - 7.1	100		96	110	4726005	4726095	4726145	4726055
16	6.7 - 8.4	100		153.6	170	4726006	4726096	4726146	4726056
25	8.4 - 10.6	100		240	290	4726007	4726097	4726147	4726057
35	9.7 - 12.1			336	380	4726008	4726098	4726148	4726058
50	11.5 - 14.4			480	530	4726009	4726099	4726149	4726059
70	13.2 - 16.6			672	750	4727001	4727091	4727141	4727051
95	15.1 - 18.8			912	1000	4727002	4727092	4727142	4727052

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	green	yellow	violet	red
1.5	2.8 - 3.5	100		14.4	20	4726121	4726111	4726071	4726041
1.5	2.8 - 3.5		1500	14.4	20	4726121K	4726111K	4726071K	4726041K
2.5	3.4 - 4.3	100		24	32	4726122	4726112	4726072	4726042
2.5	3.4 - 4.3		900	24	32	4726122K	4726112K	4726072K	4726042K
4	3.9 - 4.9	100		38.4	45	4726123	4726113	4726073	4726043
4	3.9 - 4.9		600	38.4	45	4726123K	4726113K	4726073K	4726043K
6	4.4 - 5.5	100		57.6	65	4726124	4726114	4726074	4726044
6	4.4 - 5.5		400	57.6	65	4726124K	4726114K	4726074K	4726044K
10	5.7 - 7.1	100		96	110	4726125	4726115	4726075	4726045
16	6.7 - 8.4	100		153.6	170	4726126	4726116	4726076	4726046
25	8.4 - 10.6	100		240	290	4726127	4726117	4726077	4726047
35	9.7 - 12.1			336	380	4726128	4726118	4726078	4726048
50	11.5 - 14.4			480	530	4726129	4726119	4726079	4726049
70	13.2 - 16.6			672	750	4727121	4727111	4727071	4727041
95	15.1 - 18.8			912	1000	4727122	4727112	4727072	4727042

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	blue/white	pink
1.5	2.8 - 3.5	100		14.4	20		4726081
1.5	2.8 - 3.5		1500	14.4	20	4726261K	4726081K
2.5	3.4 - 4.3	100		24	32		4726082
2.5	3.4 - 4.3		900	24	32	4726262K	4726082K
4	3.9 - 4.9	100		38.4	45		4726083
4	3.9 - 4.9		600	38.4	45		4726083K
6	4.4 - 5.5	100		57.6	65		4726084
6	4.4 - 5.5		400	57.6	65		4726084K
10	5.7 - 7.1	100		96	110		4726085
16	6.7 - 8.4	100		153.6	170		4726086
25	8.4 - 10.6	100		240	290		4726087
35	9.7 - 12.1			336	380		4726088
50	11.5 - 14.4			480	530		4726089
70	13.2 - 16.6			672	750		4727081
95	15.1 - 18.8			912	1000		4727082

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
 Packaging size: Coil ≤ 30 kg, otherwise drum  
 Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
 \*for conventional use, \*\*for careful bending; „OD“ = outer diameter

#### Similar products

- ÖLFLEX® HEAT 125 SC refer to page 196