Compact range

The compact range is designed to be our most efficient solution when it comes to assembly and cost, suitable for the most demanding environments. It can also be combined with the modular range to cover the needs of additional flexibility.

General construction

- 'All-in-one' design
- Same front as modular range
- 42mm built in depth
- Up to 2 electrical contacts
- · Metal or black plastic look

Product features

- Suitable in the toughest environments IP 66, 67 and 69K
- Wiping action gives high performance with low energies
- UL/NEMA Type 1,3R,4,4X,12,13

Operators

- Pushbuttons (illuminated and non-illuminated)
- Emergency stops (twist, pull and key release)
- Machine stops (twist, pull and key release)
- Selector switches (2 and 3 position)
- Mushrooms

Pilot lights

- Integrated LED (wide range of voltages)
- · BA9s base for filament bulb or LED



Buzzers*







CB1-610Y



Illuminated

Description	Lights and sound output	Rated current mA	Luminance mcd	Factory code	Order code
Rated voltage 24	1 V AC/DC				
• Green	Continuous	48	126	1SFA619600R6002	CB1-600G
• Red	Pulsation	53	60	1SFA619600R6101	CB1-610R
Yellow	Pulsation	53	60	1SFA619600R6103	CB1-610Y
Rated voltage 11	10-130 V AC				
• Green	Continuous	55	126	1SFA619600R6012	CB1-601G
• Red	Pulsation	70	60	1SFA619600R6111	CB1-611R
Yellow	Pulsation	70	60	1SFA619600R6113	CB1-611Y
Rated voltage 11	10-130 V DC				
Green	Continuous	15	126	1SFA619600R6022	CB1-602G
• Red	Pulsation	15	60	1SFA619600R6121	CB1-612R
Yellow	Pulsation	15	60	1SFA619600R6123	CB1-612Y
Rated voltage 23	30 V AC				
• Green	Continuous	55	126	1SFA619600R6032	CB1-603G
• Red	Pulsation	70	60	1SFA619600R6131	CB1-613R
Yellow	Pulsation	70	60	1SFA619600R6133	CB1-613Y

Non-illuminated

Description	Lights and sound output	Rated current mA	Luminance mcd	Factory code	Order code
Rated voltage 24	1 V AC/DC				
Black	Continuous	40	_	1SFA619600R6206	CB1-620B
● Black	Pulsation	48	_	1SFA619600R6306	CB1-630B
Rated voltage 11	10-130 V AC				
● Black	Continuous	40	_	1SFA619600R6216	CB1-621B
Black	Pulsation	48	-	1SFA619600R6316	CB1-631B
Rated voltage 11	10-130 V DC				
Black	Continuous	15	_	1SFA619600R6226	CB1-622B
● Black	Pulsation	15	_	1SFA619600R6326	CB1-632B
Rated voltage 23	30 V AC				
Black	Continuous	40	_	1SFA619600R6236	CB1-623B
● Black	Pulsation	40	_	1SFA619600R6336	CB1-633B

^{*} Sound level ≥ 90 db/10 cm

Heavy duty pushbuttons





Colours	● Red	Green	● Black
Replace ■ in Order code with	R	G	В
Replace ☐ in Factory code with	1	2	6



Heavy duty pushbutton

Description	Factory code	Order code
2NO	1SFA619105R102□	CP6-10 ■- 20
2NC	1SFA619105R105	CP6-10■-02
1NO+1NO	1SFA619105R107	CP6-10■-11