



**Info**

- CPR: Article number choice under [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)
- For nominal voltage U0/U: 300/500V and conductor cross-sections below 2,5mm<sup>2</sup> see ÖLFLEX® CLASSIC 100 300/500V

**Technical data**

- Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC001578  
ETIM 5.0/6.0 Class-Description: Flexible cable
- Core identification code**  
Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9  
From 6 cores: ÖLFLEX® colour code, refer to Appendix T7
- Conductor stranding**  
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Torsion movement in WTG**  
TW-0 & TW-1, refer to Appendix T0
- Minimum bending radius**  
Occasional flexing: 15 x outer diameter  
Fixed installation: 4 x outer diameter
- Nominal voltage**  
U0/U: 450/750 VAC  
In protected and fixed installations: U0/U: 600/1000 V
- Test voltage**  
4000 V
- Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor
- Temperature range**  
Occasional flexing: -5°C to +70°C  
Fixed installation: -40°C to +80°C



**ÖLFLEX® CLASSIC 100 450/750 V**  
Colour-coded PVC power and control cable

**Benefits**

- High electrical performance due to 4 kV test voltage
- High flexibility due to short-twisted conductor layers

**Application range**

- Plant engineering  
Industrial machinery  
Heating and air-conditioning systems  
Power stations
- Dry or damp rooms that are subject to medium mechanical loads
- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

**Product features**

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1

**Norm references / Approvals**

- Based on IEC 60227-5 and EN 50525-2-51

**Product Make-up**

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Cores twisted in layers
- PVC outer sheath, grey (similar RAL 7001)

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® CLASSIC 100 450/750 V</b>				
0010086	2 X 2,5	8.9	48	128
0010087	3 G 2,5	9.6	72	162
00100933	3 X 2,5	9.6	72	162
00100883	4 G 2,5	10.7	96	203
00100893	5 G 2,5	11.8	120	242
0010091	7 G 2,5	13.1	168	321
0010092	8 G 2,5	15.8	192	385
0010100	2 X 4	10.4	76.8	187
0010210	3 G 4	11.2	115.2	244
00101013	4 G 4	12.5	154	297
00101023	5 G 4	13.7	192	355
0010103	7 G 4	15.2	269	471
0010105	3 G 6	12.6	173	318
00101063	4 G 6	13.8	230	394
00101073	5 G 6	15.6	288	489
0010108	7 G 6	17.3	403	651
0010301	3 G 10	15.9	288	516
00101093	4 G 10	17.6	384	650
00101103	5 G 10	19.7	480	792
0010111	7 G 10	21.7	672	1058
0010302	3 G 16	18.3	461	728

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
00101123	4 G 16	20.4	614	1087
00101133	5 G 16	22.8	768	1118
0010303	3 G 25	23.0	720	1388
00101153	4 G 25	25.4	960	1582
00101163	5 G 25	28.5	1200	1771
0010304	3 G 35	25.6	1008	1766
00101173	4 G 35	28.5	1344	2106
00101183	5 G 35	31.9	1680	2635
0010305	3 G 50	31.0	1440	2556
00101193	4 G 50	34.5	1920	2943
00103133	5 G 50	38.6	2400	3936
0010306	3 G 70	35.3	2016	3182
00101203	4 G 70	39.4	2688	4092
00103143	5 G 70	44.1	3360	4800
0010307	3 G 95	41.3	2736	4675
00101213	4 G 95	45.8	3648	5290
00103153	5 G 95	51.6	4560	5600
0010308	3 G 120	47.6	3456	5626
00103093	4 G 120	53.1	4608	6994
00103113	4 G 150	57.4	5760	7500
00103123	4 G 185	62.8	7104	8300

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Single lengths for sizes: ≥ 5G50 max. 500 m; ≥ 5G95 max. 400; ≥ 3G120 max. 500 m; ≥ 4G120 max. 300; ≥ 4G185 max. 250 m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

**Similar products**

- ÖLFLEX® CLASSIC 100 300/500 V refer to page 27
- ÖLFLEX® CLASSIC 100 H refer to page 60
- ÖLFLEX® CLASSIC 100 BK 0,6/1 kV refer to page 33

**Accessories**

- SKINTOP® CLICK refer to page 687
- Detectable Cable ties refer to page 1042
- TY - FAST® cable ties refer to page 1041
- STAR STRIP stripping tool refer to page 985