



i Info

- CPR: Article number choice under www.lappkabel.com/cpr
- EMC-compliant

ÖLFLEX® CLASSIC 100 CY

Colour-coded and screened PVC control cable



Technical data

Classification ETIM 5/6
ETIM 5.0/6.0 Class-ID: EC001578
ETIM 5.0/6.0 Class-Description: Flexible cable

Core identification code
Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9
From 6 cores: ÖLFLEX® colour code, refer to Appendix T7

Conductor stranding
Fine wire according to VDE 0295, class 5/IEC 60228 class 5

Minimum bending radius
Occasional flexing: 20 x outer diameter
Fixed installation: 6 x outer diameter

Nominal voltage
Up to 1.0 mm²: U0/U: 300/500 V
From 1.5 mm²: U0/U: 450/750 V
Fixed, protected installation:
U0/U: 600/1000 V

Test voltage
4000 V

Protective conductor
G = with GN-YE protective conductor
X = without protective conductor

Temperature range
Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

- Benefits**
- Space-saving installation due to small cable diameters
 - High electrical performance due to 4 kV test voltage
- Application range**
- Plant engineering
Industrial machinery
Heating and air-conditioning systems
 - Conveyor and transport systems
 - Servo drives
 - In EMC-sensitive environments (electromagnetic compatibility)

- Norm references / Approvals**
- Based on IEC 60227-5 and EN 50525-2-51

- Product Make-up**
- Fine-wire strand made of bare copper wires
 - PVC insulation LAPP P8/1
 - Cores twisted in layers
 - PVC inner sheath, grey
 - Tinned-copper braiding
 - PVC outer sheath, transparent

- Product features**
- Flame-retardant according IEC 60332-1-2
 - Good chemical resistance, see catalogue appendix T1
 - High degree of screening
low transfer impedance
(max. 250 Ω/km at 30 MHz)

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 CY; U0/U: 300/500 V				
0035001	2 X 0,5	7.0	41	75
0035002	3 G 0,5	7.3	46	83
00350033	4 G 0,5	7.9	55	99
00352013	5 G 0,5	8.4	66	112
0035202	7 G 0,5	8.9	80	132
0035004	2 X 0,75	7.4	46	86
0035005	3 G 0,75	7.9	57	100
00350063	4 G 0,75	8.4	64	115
00350163	5 G 0,75	8.9	77	130
0035203	7 G 0,75	9.7	102	161
0035220	2 X 1,0	7.9	56	98
0035221	3 G 1,0	8.2	65	111
00352223	4 G 1,0	8.7	78	130
00352233	5 G 1,0	9.5	89	153
0035204	7 G 1,0	10.2	113	185
ÖLFLEX® CLASSIC 100 CY; U0/U: 450/750 V				
0035000	2 X 1,5	9.9	65	132
0035458	3 G 1,5	10.3	79	170
00354593	4 G 1,5	11.3	97	204
00354603	5 G 1,5	12.6	116	246
0035461	7 G 1,5	13.9	149	320
0035011	3 G 2,5	11.8	146	211
00350173	4 G 2,5	13.5	167	310
00350123	5 G 2,5	14.6	200	326

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
0035289	7 G 2,5	15.9	288	444
00350183	4 G 4	15.1	237	403
00350133	5 G 4	16.5	328	478
00350193	4 G 6	16.6	318	521
00350143	5 G 6	18.2	441	624
0034953	3 G 10	18.9	414	690
00350213	4 G 10	21.1	558	843
00352903	5 G 10	23.1	714	1004
0034954	3 G 16	21.7	607	910
00350223	4 G 16	23.9	804	1164
00350153	5 G 16	26.8	1050	1812
0034955	3 G 25	26.6	936	1330
00350233	4 G 25	29.4	1289	1903
00350243	5 G 25	32.6	1446	2374
0034956	3 G 35	29.4	1258	1370
00350253	4 G 35	32.4	1693	2489
00350263	5 G 35	36.0	1975	2771
0034952	3 G 50	35.1	1748	2590
00350273	4 G 50	38.8	2342	3362
00350283	4 G 70	43.7	3035	3719
00350293	4 G 95	50.4	4055	5849
00354303	4 G 120	56.8	5225	7509
00354313	4 G 150	62.2	6300	7800
00354323	4 G 185	67.8	7753	9866

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Single lengths for sizes: ≥ 4G50 max. 500 m; ≥ 4G95 max. 400 m; ≥ 4G120 max. 300 m; ≥ 4G150 max. 250 m
Photographs and graphics are not to scale and do not represent detailed images of the respective products.

- Similar products**
- ÖLFLEX® SERVO 9YSLCY-JB refer to page 98
 - ÖLFLEX® SERVO 2YSLCY-JB refer to page 97

- Accessories**
- SKINTOP® BRUSH ADD-ON refer to page 700
 - 3M Scotch™ 1183 screening tape refer to page 1030
 - SKINTOP® MS-HF-M BRUSH refer to page 708
 - SKINTOP® MS-M BRUSH refer to page 702