



JE-LiYCY...BD

Screened data transmission cable for industrial electronics



Info

- In accordance with DIN VDE 0815

JE-LiYCY...BD EB

Screened data transmission cable for industrial electronics



Info

- Blue version:
Hazard protection type -i- is required where there is a risk of explosion

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC000829 ETIM 5.0/6.0 Class-Description: Signal-/telecommunications cable
	Core identification code according to VDE 0815, refer to Appendix T10
	Mutual capacitance max. 100 nF/km
	Peak operating voltage (not for power applications) 225 V
	Coupling approx. 200 pF/100 m
	Inductivity approx. 0.65 mH/km
	Conductor stranding Multi-wire, 7 x 0.3mm
	Minimum bending radius Occasional flexing: 15 x outer diameter Fixed installation: 5 x outer diameter
	Test voltage JE-LiYCY...BD Core/core: 500 V Core/screen: 2000 V JE-LiYCY...BD EB Core/Core: 1000 V Core/screen: 2000 V
	Loop resistance max. 78.4 Ω/km
	Temperature range Occasional flexing: -5°C to +50°C Fixed installation: -30°C to +70°C

Benefits

- Can be used for Maxi TERMI-POINT® wiring
- Overall braid minimises electrical interference
- Decoupling of circuits by means of twisted-pair (TP) design (crosstalk effects)

Application range

- Connection cable for use in electronics and in measurement, control and signal applications
- This cable is also used as a pulse and data transmission cable
- JE-LiYCY...BD has also proved to be an efficient connection cable for telephone systems, e.g. paging and intercom systems.
- For fixed installation on and under plaster, in dry and damp rooms
- For outdoor use this cable should be installed under plaster only

Product features

- The 2-pair version (2 x 2 x 0.5) is twisted into a star quad
- Flame-retardant according IEC 60332-1-2
- JE-LiYCY...BD EB:
For intrinsically safe circuits (type of protection i - intrinsic safety) according to IEC 60079-14:2013 / EN 60079-14:2014 / VDE 0165-1:2014, section 16.2.2

Norm references / Approvals

- In accordance with DIN VDE 0815 type JE-LiYCY...BD

Product Make-up

JE-LiYCY...BD

- 7-wire bare stranded copper conductor
- Core insulation made of PVC
- 2 cores twisted into a pair, and 4 pairs into units (for 2 x 2 x 0.5 as star quad cable)
- Bundles twisted in layers, foil wrapping, screening braid made of tinned copper wires
- Outer sheath made of PVC
Outer sheath colour: pebble grey (RAL 7032)

JE-LiYCY...BD EB

- 7-wire bare stranded copper conductor
- Core insulation made of PVC
- 2 cores twisted into a pair, and 4 pairs into units (for 2 x 2 x 0.5 as star quad cable)
- Bundles twisted in layers, foil wrapping, screening braid made of tinned copper wires
- Outer sheath made of PVC
Outer sheath colour: sky blue (RAL 5015)

Article number	Number of pairs and conductor cross section (mm ²)	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
JE-LiYCY...BD				
0034200	2 x 2 x 0.5	7.5	51	70
0034201	4 x 2 x 0.5	10	87	155
0034202	8 x 2 x 0.5	13	144	260
0034208	12 x 2 x 0.5	15.5	195	340
0034203	16 x 2 x 0.5	17	249	430
0034210	20 x 2 x 0.5	18.5	298	495
0034204	24 x 2 x 0.5	20.5	348	605
0034212	32 x 2 x 0.5	22.5	441	738
JE-LiYCY...BD EB, blue outer sheath				
0034220	2 x 2 x 0.5	7.5	51	95
0034221	4 x 2 x 0.5	10	87	155
0034222	8 x 2 x 0.5	13	144	260
0034223	12 x 2 x 0.5	15.5	193	340
0034224	16 x 2 x 0.5	17	249	430
0034225	20 x 2 x 0.5	18.5	298	495
0034226	24 x 2 x 0.5	20.5	348	605
0034227	32 x 2 x 0.5	22.5	441	738
0034228	40 x 2 x 0.5	24	531	845

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

MAXI-TERMI-POINT® is a registered trademark of AMP

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Accessories

- SKINTOP® MS-HF-M SC refer to page 707
- SKINTOP® MS-SC-M refer to page 701
- UNIVERSAL STRIP stripping tool refer to page 990
- STAR STRIP stripping tool refer to page 985