



ASI Distributor

AS-Interface Distributor



Benefits

- Cost-efficient and rational wiring for AS-Interface installations
- Space-saving due to compact dimensions
- Easy to install

Product features

- Field mountable distributor with flat cable clamp
- On 2 flat cables or straight M12 socket (A-coded)
- Suitable for drag chains
- Panel mounting
- Rated current ≤ 4 A (H-distributor: $I \leq 8$ A)

Product Make-up

- Wire cross-section: 0,34 mm²
- Colour-code: bn (1), wh (2), bu (3), bk (4)
- Outer sheath: PUR halogen-free, black

Suitable cables

- UNITRONIC® BUS ASI Page 328
- UNITRONIC® BUS ASI FD Page 329

Technical data

Classification ETIM 5/6
 ETIM 5.0/6.0 Class-ID: EC002585
 ETIM 5.0/6.0 Class-Description:
 Passive sensor-actuator interface

Connection type
 Penetration technique for flat cable

Protection rating
 IP 67
 (H-distributor: IP69)

Ambient temperature (operation)
 -25 °C to +75 °C

| Article number | Article designation | Length (m) | PU |
|---|----------------------------|------------|----|
| Distribution of 1 flat cable | | | |
| on 2 flat cables (H distributor) | | | |
| 22260802 | AB-ASI-J-Y-Y-N | | 1 |
| on M12 socket (2-pos.) | | | |
| 22260800 | AB-ASI-J-Y-N-M12FS | | 1 |
| 22260803 | AB-ASI-J-Y-N-PUR-1,0-M12FS | 1 | 1 |
| 22260804 | AB-ASI-J-Y-N-PUR-2,0-M12FS | 2 | 1 |
| Distribution of 2 flat cables | | | |
| on M12 socket (4-pos.) | | | |
| 22260801 | AB-ASI-J-Y-B-M12FS | | 1 |
| 22260805 | AB-ASI-J-Y-B-PUR-1,0-M12FS | 1 | 1 |
| 22260806 | AB-ASI-J-Y-B-PUR-2,0-M12FS | 2 | 1 |

Copper price basis: inclusive of copper. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Accessories

- Kraftform® adjustable torque screwdriver/Kraftform Kompakt® Set refer to page 1060