




## EPIC® SENSOR Flush-type M8



### Benefits

- Flexible connection solutions for individual device concepts
- Simple installation in devices (e.g. cabinet)

### Application range

- Connection of enclosures and cabinets

### Product features

- M8 fastening thread
- Designs for front mounting
- PWIS-free

### Product Make-up

- TPE single strands, l = 0.5 m
- Core cross section: 0.25 mm<sup>2</sup>

### Technical data



#### Classification ETIM 5/6

ETIM 5.0/6.0 Class-ID: EC002061  
ETIM 5.0/6.0 Class-Description:  
Sensor-actuator connector chassis



#### Material

Contact: CuSn  
Contact surface: Ag



#### Protection rating

IP 67



#### Ambient temperature (operation)

Plug/socket  
-25 °C to +85 °C

#### Coding

A-standard

#### Rated current (A)

4 A

Article number	Article designation	Number of pins	Rated voltage (V)	PU
<b>Panel-mount connector male</b>				
22260100	AB-C3-M8MS-0,5	3	60	1
22260101	AB-C4-M8MS-0,5	4	30	1
<b>Panel-mount connector female</b>				
22260102	AB-C3-M8FS-0,5	3	60	1
22260103	AB-C4-M8FS-0,5	4	30	1

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

### Accessories

- Matching fitting nut: 22260104