



EPIC® H-BE 10 Screw termination

The proven standard inserts for easy assembly



Info

- Proven screw for easy installation
- Screw, crimp, cage clamp and Push-In version - freely combinable
- Railway applications

EPIC® H-BE 10 Crimp termination

The proven standard inserts for easy assembly



Info

- For wire connection up to 4 mm²
- Screw, crimp, cage clamp and Push-In version - freely combinable

EPIC® H-BE 10 Cage clamp

The proven standard inserts for easy assembly



Info

- Multifunctional insert for versatile applications
- Screw, crimp, cage clamp and Push-In version - freely combinable

EPIC® H-BE 10 Push-In termination

The proven standard inserts for easy assembly



Info

- Push-In version - fast and easy tool free connection technology
- Screw, crimp, cage clamp and Push-In version - freely combinable
- Multifunctional insert for versatile applications

Suitable housing

- EPIC® ULTRA H-B 10
- EPIC® H-B 10 Housings
- EPIC® QUICK & EASY Mounting system
- Refer to Selection Table A10 to select the required inserts and housings

Suitable contacts:

EPIC® H-BE 10 Crimp termination

- EPIC® H-BE 2.5 machined contacts
- Page 590

Benefits

- Standard inserts with screw, crimp cage clamp and Push-In termination
- The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents

EPIC® H-BE 10 Screw termination

- Railway applications
- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL4
- UL tested for application in control cabinets according UL 508 / UL 2237

EPIC® H-BE 10 Push-In termination

- Insertion of cores with end sleeves in Push-In inserts gives mounting safety and time saving without any tools
- Easy dismantling and insertion of wires by pushing the orange button
- Test socket for standard 2mm test tip for easy testing of Push-In inserts
- Railway applications
- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL4

Application range

- Mechanical engineering
- Plastics industry
- Light & sound technology

EPIC® H-BE 10 Screw termination

EPIC® H-BE 10 Push-In termination

- Railway applications / vehicle construction

Suitable tools

EPIC® H-BE 10 Screw termination

- Kraftform® adjustable torque screwdriver / Kraftform Kompakt® Set refer to page 1060

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC000438 ETIM 5.0/6.0 Class-Description: Contact insert for industrial connectors		Termination methods EPIC® H-BE 10 Screw termination Screw termination: 0.5 - 2.5 mm ² EPIC® H-BE 10 Crimp termination Crimp termination: 0.5 - 4.0 mm ² EPIC® H-BE 10 Cage clamp Cage clamp termination: 0.5 - 2.5 mm ² EPIC® H-BE 10 Push-In termination Push-In termination: 0.14 - 2.5mm ²
	Rated voltage (V) IEC: 500 VUL: 600 VCSA: 600 V		Stripping length (mm) EPIC® H-BE 10 Screw termination 8
	Rated impulse voltage 6 kV		EPIC® H-BE 10 Cage clamp 7
	Rated current (A) EPIC® H-BE 10 Screw termination EPIC® H-BE 10 Crimp termination EPIC® H-BE 10 Cage clamp IEC: 16 A UL: 16 A CSA: 16 A IEC: 16 A UL: 16 A CSA: 16 AEPIC® H-BE 10 Push-In termination IEC: 16 A UL: 13 A CSA: 13 A		Material EPIC® H-BE 10 Screw termination PC, polycarbonate EPIC® H-BE 10 Crimp termination PC, polycarbonate EPIC® H-BE 10 Push-In termination PA Polyamid
	Pollution degree 3		Cycle of mechanical operation EPIC® H-BE 10 Screw termination 500
	Flammability EPIC® H-BE 10 Screw termination EPIC® H-BE 10 Crimp termination EPIC® H-BE 10 Push-In termination UL94 V-0 EPIC® H-BE 10 Cage clamp UL94 V-2		EPIC® H-BE 10 Screw termination Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770 and E483837
	Contact resistance EPIC® H-BE 10 Screw termination < 2 mOhm EPIC® H-BE 10 Crimp termination < 2 mOhm EPIC® H-BE 10 Cage clamp 1.5 - 4 mohm EPIC® H-BE 10 Push-In termination < 2 mOhm		EPIC® H-BE 10 Crimp termination Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770
	Contacts EPIC® H-BE 10 Screw termination Copper alloy, hard silver-plated EPIC® H-BE 10 Crimp termination Copper alloy, hard silver/gold-plated EPIC® H-BE 10 Cage clamp Copper alloy, hard silver-plated EPIC® H-BE 10 Push-In termination Copper alloy, hard silver-plated		EPIC® H-BE 10 Push-In termination UL-tested: UL File Number: E75770
	Number of contacts 10 + PE		Temperature range -40°C to +100°C, short-term up to +125°C

Article number	Article description	Contact type	Wire protection	Number of operating contacts	Pieces / PU
H-BE 10 screw termination					
10192000	EPIC® H-BE 10 SS	male	yes	1 - 10	10
10193000	EPIC® H-BE 10 BS	female	yes	1 - 10	10
10192100	EPIC® H-BE 10 SS	male		1 - 10	10
10193100	EPIC® H-BE 10 BS	female		1 - 10	10
H-BE 10 crimp termination					
10182000	EPIC® H-BE 10 SCM	male		1 - 10	10
10183000	EPIC® H-BE 10 BCM	female		1 - 10	10
H-BE 10 cage clamp termination					
10400100	EPIC® H-BE 10 SF	male	yes	1 - 10	10
10401100	EPIC® H-BE 10 BF	female	yes	1 - 10	10
H-BE 10 Push-In termination					
44423202	EPIC® H-BE 10 SP	male	yes	1 - 10	10
44423203	EPIC® H-BE 10 BP	female	yes	1 - 10	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.