AFFENDIA

Rectangular connectors • EPIC® MH modular system module













& LAPP

EPIC® MH 17

High flexibility by the use of any combination of inserts in one connector







Info

- Modular connector system, plugable with the market standard
- Universal module for 17 contacts in smallest space

Suitable housing

- EPIC MH 6 R Page 570
- EPIC MH 10 R Page 570
- EPIC MH 16 R Page 570
- EPIC MH 24 R Page 570
- EPIC® H-B housing use in high version

Suitable contacts:

 EPIC® H-D 1.6 machined contacts Page 587

Benefits

- Universal module for 17 contacts in smallest space
- Crimp connection for permanent vibration proof contact
- EPIC® MH system is mateable with the market standard
- The mix of different functions in one plug guarantees high flexibility
- Railway applications
 - Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL4

Application range

- Mechanical engineering
- · Robotics industry
- · Plant engineering
- Renewable energy
- Railway applications / vehicle construction

Technical data



Classification ETIM 5/6

ETIM 5.0/6.0 Class-ID: EC002641 ETIM 5.0/6.0 Class-Description: Modular connector (industrial connector)



Rated voltage (V) 160 V

Rated impulse voltage 2.5 kV



Rated current (A)

Pollution degree

Flammability UL94 V-0 **Contact resistance**

< 5 mOhm

#

Number of contacts 17

_

Termination methods Crimp termination: 0.14 - 2.5 mm²



Material

Polyamide, glass fibre-reinforced



Cycle of mechanical operation

→ 500

Certifications

UL-tested:

UL File Number: E75770

0#

Temperature range -40°C

+125°C

Article number	Article description	Contact type	Number of operating contacts	Slots	Pieces / PU
EPIC® MH 17					
44423224	EPIC® MHS 17 CM	male	17	1	10
44423225	EPIC® MHB 17 CM	female	17	1	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.