



EPIC® MH 1.0mm contacts stamped

The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.



Info

- Stamped gold plated contacts with 1.0mm diameter for D-Sub inserts

Benefits

- Stamped gold plated contacts with 1.0mm diameter for D-Sub inserts
- Gold-plated contacts for low transfer resistance

Application range

- Mechanical and plant engineering
- Robotics industry
- Renewable energy
- Railway applications / vehicle construction

Technical data



Termination methods

Crimp termination

Stripping length (mm)

3 ± 0.5



Material

brass gold plated CuZn / Au



Cycle of mechanical operation

500

| Article number | Article description | Contact type | Conductor cross-section AWG | Pieces / PU |
|--|---|--------------|-----------------------------|-------------|
| EPIC® MH 1.0mm contacts stamped | | | | |
| 44423320 | EPIC® MH SCEG AU 0.09 - 0.25sqmm D=1.0 | male | 28 - 24 | 100 |
| 44423322 | EPIC® MH BCEG AU 0.09 - 0.25sqmm D=1.0 | female | 28 - 24 | 100 |
| 44423321 | EPIC® MH SCEG AU 0.25 - 0.52 sqmm D=1.0 | male | 24 - 20 | 100 |
| 44423323 | EPIC® MH SCEG AU 0.25 - 0.52 sqmm D=1.0 | female | 24 - 20 | 100 |

Photographs and graphics are not to scale and do not represent detailed images of the respective products.



EPIC® MH 1.0mm contacts machined

The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.



Info

- Machined gold plated contacts with 1mm diameter for EPIC® MH Gigabit module
- Gold-plated contacts for low transfer resistance

Benefits

- Machined gold plated contacts with 1mm diameter for EPIC® MH Gigabit module
- Gold-plated contacts for low transfer resistance

Application range

- Mechanical and plant engineering
- Robotics industry
- Renewable energy
- Railway applications / vehicle construction

Technical data



Stripping length (mm)

4.2 ± 0.5mm



Material

brass gold plated CuZn / Au



Cycle of mechanical operation

500

| Article number | Article description | Contact type | Conductor cross-section AWG | Pieces / PU |
|---|--|--------------|-----------------------------|-------------|
| EPIC® MH 1.0mm contacts machined | | | | |
| 44423285 | EPIC® MH SCEM AU 0.09 - 0.25sqmm D=1.0 | male | 28 - 24 | 100 |
| 44423286 | EPIC® MH BCEM AU 0.09 - 0.25sqmm D=1.0 | female | 28 - 24 | 100 |
| 44423287 | EPIC® MH SCEM AU 0.13 - 0.33sqmm D=1.0 | male | 26 - 22 | 100 |
| 44423288 | EPIC® MH BCEM AU 0.13 - 0.33sqmm D=1.0 | female | 26 - 22 | 100 |
| 44423289 | EPIC® MH SCEM AU 0.25 - 0.52sqmm D=1.0 | male | 24 - 20 | 100 |
| 44423290 | EPIC® MH BCEM AU 0.25 - 0.52sqmm D=1.0 | female | 24 - 20 | 100 |

Photographs and graphics are not to scale and do not represent detailed images of the respective products.