



EPIC® SIGNAL M23 Inserts 8+1 pole

Inserts for M23 circular connectors



EPIC® SIGNAL M23 Inserts 9 pole

Inserts for M23 circular connectors



Suitable housing

- EPIC® SIGNAL M23 A1 Page 639
- EPIC® SIGNAL M23 A1 D3.2 Page 639
- EPIC® SIGNAL M23 A3 Page 639
- EPIC® SIGNAL M23 G4 Page 640
- EPIC® SIGNAL M23 G5 Page 640
- EPIC® SIGNAL M23 G6 Page 640
- EPIC® SIGNAL M23 B1 Page 641
- EPIC® SIGNAL M23 B2 Page 641
- EPIC® SIGNAL M23 D6 Page 643
- EPIC® SIGNAL M23 F6 Page 643
- EPIC® SIGNAL M23 F7 Page 643
- All inserts fit into all housings

Suitable contacts:

- EPIC® SIGNAL M23 Contacts male Page 649
- EPIC® SIGNAL M23 Contacts female Page 649

EPIC® SIGNAL M23 Inserts 8+1 pole

- 8+1: 8*1 mm contact, 1*2 mm contact

EPIC® SIGNAL M23 Inserts 9 pole

- 9: 9*1 mm contact

Benefits

- Universal further processing of the M23 inserts through different packaging units. Fully assembled with suitable solder contacts or unpopulated for individual assembly with crimp or solder contacts

Application range

- Plant engineering
- Measurement and control technology
- Apparatus construction

Technical data

Classification ETIM 5/6
 ETIM 5.0/6.0 Class-ID: EC000438
 ETIM 5.0/6.0 Class-Description:
 Contact insert for industrial connectors

Rated voltage (V)
 according to IEC 61984: 150 V

Rated impulse voltage
EPIC® SIGNAL M23 Inserts 8+1 pole
 2.5 kV
EPIC® SIGNAL M23 Inserts 9 pole
 1.5 kV

Rated current (A)
EPIC® SIGNAL M23 Inserts 8+1 pole
 20 A (2 mm contact)
 7 A (1 mm contacts)
EPIC® SIGNAL M23 Inserts 9 pole
 7 A

Pollution degree
 3

Contact resistance
 < 4 mOhm

Contacts
 Gold-plated brass

Number of contacts
EPIC® SIGNAL M23 Inserts 8+1 pole
 8 + 1
EPIC® SIGNAL M23 Inserts 9 pole
 9

Termination methods
EPIC® SIGNAL M23 Inserts 8+1 pole
 Crimp termination: 0.14 - 1.0 mm²
 (1.0 - 2.5 mm² for 2-mm contact)
 Solder termination: up to 1.0 mm²
 (up to 2.5 mm² for 2-mm contact)
EPIC® SIGNAL M23 Inserts 9 pole
 Crimp termination: 0.14 - 1.0 mm²
 Solder termination: up to 1.0 mm²

Cycle of mechanical operation
 100

VDE-tested
 Certified production control:
 VDE-REG. no. C24 (according to
 EN 61984, SELV according to DIN
 VDE 0100-410 has to be guaranteed)
 UL File Number: E249137

Temperature range
 -25°C up to +125°C

Article number	Article description	Inserts	Contacts included	Pin configuration	Pieces / PU
8+1-pin inserts, P-part = rotation to the left (plug side anticlockwise)					
73002736	P-part	without contacts		8+1	5
73002737	P-part	without contacts		8+1	20
73002738	P-part	+ male contacts, solder	9	8+1	5
73002739	P-part	+ male contacts, solder	9	8+1	20
73002740	P-part	+ female contacts, solder	9	8+1	5
73002741	P-part	+ female contacts, solder	9	8+1	20
8+1-pin inserts, E-part = rotation to the right (plug side clockwise)					
73002742	E-Part	without contacts		8+1	5
73002743	E-Part	without contacts		8+1	20
73002744	E-Part	+ male contacts, solder	9	8+1	5
73002745	E-Part	+ male contacts, solder	9	8+1	20
73002746	E-Part	+ female contacts, solder	9	8+1	5
73002747	E-Part	+ female contacts, solder	9	8+1	20
9-pin inserts, P-part = rotation to the left (plug side anticlockwise)					
73002724	P-part	Unpopulated		9	5
73002725	P-part	Unpopulated		9	20
73002726	P-part	+ male contacts, solder	9	9	5
73002727	P-part	+ male contacts, solder	9	9	20
73002728	P-part	+ female contacts, solder	9	9	5
73002729	P-part	+ female contacts, solder	9	9	20
9-pin inserts, E-part = rotation to the right (plug side clockwise)					
73002730	E-Part	Unpopulated		9	5
73002731	E-Part	Unpopulated		9	20
73002732	E-Part	+ male contacts, solder	9	9	5
73002733	E-Part	+ male contacts, solder	9	9	20
73002734	E-Part	+ female contacts, solder	9	9	5
73002735	E-Part	+ female contacts, solder	9	9	20

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-component and one E-component. P-component = left turning (anticlockwise), E-component = right turning (clockwise) / Photographs and graphics are not to scale and do not represent detailed images of the respective products.