




SKINDICHT® MINI NBR / SKINDICHT® MINI FKM



Benefits

- High degree of protection
- For the smallest conductor sizes
- Low height
- Gentle cable clamping
- High packing density

Application range

- For use wherever there is limited assembly space.
- Sensors
- Measurement and control technology

Product features

SKINDICHT® MINI FKM

- Suitable for high temperature and aggressive media surroundings

Technical data

Classification ETIM 5/6
 ETIM 5.0/6.0 Class-ID: EC000441
 ETIM 5.0/6.0 Class-Description: Cable screw gland

Caution
 Recommendation of torque
 M 6 x 1 1,5 Nm
 M 8 x 1 3,0 Nm
 M 10 x 1 6,0 Nm

Material
SKINDICHT® MINI NBR
 Body: Nickel-plated brass
 Sealing: CR/NBR
SKINDICHT® MINI FKM
 Body: Nickel-plated brass
 Sealing: FKM

Protection rating
 IP 66
 IP 68 - 5 bar

Temperature range
SKINDICHT® MINI NBR
 -20°C to +100°C
SKINDICHT® MINI FKM
 -20°C up to +200°C

Article number	Article designation / size	Clamping range ØF (mm)	SW wrench size mm	Overall length, C (mm)	Thread length, D (mm)	Clear opening F (mm)	Pieces / PU
SKINDICHT® MINI NBR							
52001860	MINI 6 x 1	2 - 3	9	19.7	5	3	50
52001880	MINI 8 x 1	3,5 - 5,5	11	20.5	5	5	50
52001895	MINI 10 x 1	5 - 7	14	22.3	5	7	50
SKINDICHT® MINI FKM							
52001889	MINI 6 x 1	2 - 3	9	19.7	5	3	50
52001887	MINI 8 x 1	3,5 - 5,5	11	20.5	5	5	50
52001894	MINI 10 x 1	5 - 7	14	22.3	5	7	50

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Accessories

- SKINDICHT® SM-M refer to page 744