



## SKINDICHT® SE-M



## SKINDICHT® SE-M 220/320



### Benefits

#### SKINDICHT® SE-M

- Sealed by incised sealing ring
- Corrosion-resistant
- Easy to install
- Completely safe cable entry
- Low overall height

#### SKINDICHT® SE-M 220/320

- Combination of various conduit glands is possible depending on the type
- Low overall height
- High stability
- Two or three separate cable outlets

### Application range

- For high mechanical stress
- When no connection thread is provided

### Product Make-up

#### SKINDICHT® SE-M

- M20 x 1.5 - M25 x 1.5 with 2 screw holes
- M32 x 1.5 with 4 screw holes
- With incised sealing ring

### Note

#### SKINDICHT® SE-M 220/320

- Type SKINDICHT® SE-M 220/320 without E+D is without incised sealing ring and without compression screw
- Type SKINDICHT® SE-M 220/320 without E+D can be combined with all cable glands (incl. O-ring) such as sealing, strain-relief, anti-kink, conduit-connecting or earthing glands
- The protection class is dependent on the combination with the various special glands. The minimum standard is IP 55.

### Technical data

**Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000441  
ETIM 5.0/6.0 Class-Description: Cable screw gland

**Material SKINDICHT® SE-M**  
Body: zinc die-casting, grey, hammer tone finish  
Compression screw: nickel-plated brass  
Incised sealing ring: CR/NBR  
O-ring: NBR

**SKINDICHT® SE-M 220/320**  
Body: zinc die-casting, hammer tone finish  
Compression screw: nickel-plated brass  
Incised sealing ring: CR/NBR  
Flat sealing: SBR

**Protection rating**  
IP 55

**Temperature range**  
-20°C to +80°C

Article number	Article designation / size	Incised sealing ring ØF (mm)	Overall height (mm)	SW wrench size mm	Overall length, C (mm)	Overall width (mm)	Pieces / PU
<b>SKINDICHT® SE-M</b>							
52108000	M 20 x 1,5	4/7/10/13	31	20	49.2	42	10
52108010	M 25 x 1,5	8.5/11.5/14.5/17.5	40	25	68.2	60	5
52108020	M 32 x 1,5	16/19/22/25	51.5	32	84.2	66	1
<b>SKINDICHT® SE-M 220/320</b>							
52108040	2 x M20 x 1,5	2 x 4/7/10/13					1
52108050	3 x M20 x 1,5	3 x 4/7/10/13					1
<b>SKINDICHT® SE-M 220/320 without E+D</b>							
52108041	2 x M20 x 1,5						1
52108051	3 x M20 x 1,5						1

Photographs and graphics are not to scale and do not represent detailed images of the respective products.