



SKINDICHT® ZS-M

Benefits

- Enables the use of PG accessories in metric threads
- Assembling with a wrench

Application range

- Hexagonal converter from a metric outer thread to a PG inner thread.
- Machines
- Devices
- Housings

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Note

- SKINDICHT® ZS-M-XL offers a long metric connection thread

Technical data

Classification ETIM 5/6
 ETIM 5.0/6.0 Class-ID: EC000441
 ETIM 5.0/6.0 Class-Description: Cable screw gland

Material
 Nickel-plated brass

Temperature range
 -60°C to +200°C



Article number	Thread, male M 1	Thread, female PG/NPT	Pieces / PU
SKINDICHT® ZS-M			
52104330	12 x 1.5	7.0	100
52104340	16 x 1.5	9.0	100
52104010	16 x 1.5	11.0	100
52104360	20 x 1.5	11.0	100
52104370	20 x 1.5	13.5	100
52104380	20 x 1.5	16.0	50
52104400	25 x 1.5	21.0	50
52104410	32 x 1.5	29.0	25
52104420	40 x 1.5	36.0	10
52104430	50 x 1.5	42.0	10
52104440	63 x 1.5	48.0	10
SKINDICHT® ZS-M-XL			
52104335	12 x 1.5	7.0	100
52104345	16 x 1.5	9.0	100
52104365	20 x 1.5	11.0	100
52104375	20 x 1.5	13.5	100
52104385	20 x 1.5	16.0	50
52104405	25 x 1.5	21.0	50
52104415	32 x 1.5	29.0	25
52104425	40 x 1.5	36.0	10
52104435	50 x 1.5	42.0	10
52104445	63 x 1.5	48.0	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Accessories

- SKINDICHT® SM-M refer to page 744