



SILVYN® KLICK-RH



i Info

- One-piece conduit holder

Benefits

- Fast assembly
- Easy to disassemble
- High tensile strength
- Conduit retained by rib
- No loose parts

Application range

- In combination with protective conduit
- SILVYN® RILL PA 6
- SILVYN® RILL PA 12
- Fastening of conduits on machine walls for all applications

Product features

- Impact-resistant polyamide
- One-piece conduit holder
- Suitable for mounting onto a C-profile rail
- Stackable

Product Make-up

- One-piece conduit holder with M5/M6 borehole for fixation

Suitable conduits

- SILVYN® RILL PA 6 Page 847
- SILVYN® RILL PA 12 Page 848

Technical data

Classification ETIM 5/6
ETIM 5.0/6.0 Class-ID: EC001171
ETIM 5.0/6.0 Class-Description: Holder for protective hose

Colour delivered
Grey (RAL 7001)
Black (RAL 9005), UV-resistant

Material
PA6

Temperature range
-40 °C to +115 °C

Article number	Nominal size	Hole Ø (mm)	Suitable for SILVYN® RILL	Pieces / PU
SILVYN® KLICK-RH grey				
65500630	10	5	10	50
65500631	13	5	13	50
65500632	16	6	16	50
65500633	18	6	18	50
65500634	21	6	21	50
65500635	28	6	28	25
65500636	34	6	34	25
65500637	42	6	42	25
65500638	54	6	54	10
SILVYN® KLICK-RH black				
65500639	10	5	10	50
65500640	13	5	13	50
65500641	16	6	16	50
65500642	18	6	18	50
65500643	21	6	21	50
65500644	28	6	28	25
65500645	34	6	34	25
65500646	42	6	42	25
65500647	54	6	54	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.