

### Phillips cross-head screwdriver

according to DIN ISO 8764

PH 0 x 60	145	12	11 7130
PH 1 x 80	165	12	11 7131
PH 2 x 100	195	12	11 7132
PH 3 x 150	260	12	11 7133

### Pozidriv cross-head screwdriver

according to DIN ISO 8764 - 1

PZ 0 x 60	145	12	11 7140
PZ 1 x 80	165	12	11 7141
PZ 2 x 100	195	12	11 7142
PZ 3 x 150	260	12	11 7143

### TORX® screwdriver with bore (tamper resistant)

T 6 x 60 (without bore)	135	12	11 7306
T 7 x 60	135	12	11 7307
T 8 x 60	145	12	11 7308
T 9 x 60	145	12	11 7309
T 10 x 80	175	12	11 7310
T 15 x 80	175	12	11 7315
T 20 x 100	195	12	11 7320
T 25 x 100	195	12	11 7325
T 30 x 115	225	12	11 7330
T 40 x 115	225	12	11 7340

### Ball-end hex key (Allen wrench)

according to DIN 5265

Size 3 x 100	185	12	11 7223
Size 4 x 100	185	12	11 7224
Size 5 x 100	195	12	11 7225
Size 6 x 125	220	12	11 7226
Size 8 x 150	260	12	11 7228

### Hexagon nut driver

according to DIN 3125

Size 5 x 125	210	12	11 7204
Size 5.5 x 125	210	12	11 7205
Size 6 x 125	210	12	11 7206
Size 7 x 125	220	12	11 7207
Size 8 x 125	220	12	11 7208
Size 9 x 125	220	12	11 7209
Size 10 x 125	220	12	11 7210
Size 11 x 125	235	12	11 7211
Size 13 x 125	235	12	11 7213
Size 14 x 125	235	12	11 7214
Size 17 x 125	235	12	11 7217

### Stubby screwdrivers

with 2-component handle, for slot-head screws

5.5 x 1.0 x 38	95	12	11 0290
6.5 x 1.2 x 38	95	12	11 0294

for Phillips crosshead screws

PH 1 x 38	95	12	11 0120
PH 2 x 38	95	12	11 0122

### Slot-head screwdriver

according to DIN ISO 2380, long design

5.5 x 1.0 x 300	410	12	11 7112
-----------------	-----	----	---------