| T-handle screwdriver set, 8 pieces for applying significantly more force than with conventional screwdrivers. With screws (Allen screws). Voluminous, edge-free handle in 2-component techno | | | |
|---|---------------|---------------------|---|
| nade of tempered S2 special steel, chrome-plated, with ball-end on longer bla | ide, black s | atined, including a | a practical |
| storage stand for on the workbench or mounting on the wall. One key each of 2 – 2.5 – 3 – 4 – 5 – 6 – 8 – 10 mm | | | 11 1221 |
| | 1 | 11 0520 | Hand |
| | | | 3 |
| Hex key sets, 8 pieces | | | |
| on key ring, according to DIN 911, made of chrome vanadium steel | 4 | 11 0500 | |
| sizes 2 - 2.5 - 3 - 4 - 5 - 6 - 8 - 10 5/64" - ³ /32" - ¹ /8" - ⁵ /32" - ³ /16" - ⁷ /32" - ¹ /4" - ⁵ /16" | 1 | 11 0592 11 0594 | |
| 104 - 132 - 10 - 132 - 110 - 132 - 14 - 110 | 1 | 11 0574 | Millis a MA |
| Ball-end hex key set 7 pieces | | | |
| in a pocket-sized holder | | | |
| Sizes 2.5 - 3 - 4 - 5 - 6 - 8 - 10 | 1 | 11 0596 | date date |
| | | | |
| TORX [®] key set, 8 pieces | | | |
| in a pocket-sized holder T 9 - T 10 - T 15 - T 20 - T 25 - T 27 - T 30 - T 40 | 1 | 11 0598 | |
| · · · · · · · · · · · · · · · · · · · | | 110570 | |
| Socket wrench set, 33 pieces | | | a ame |
| $^{1/_{4}^{\prime\prime}}$ square drive, hex sockets made of chrome vanadium steel, plated with po | lished chro | me, in a metal ca | se. |
| Reversible ratchet with PosiLock holding mechanism, slide handle, 50 mm and | | | r, |
| Cardan joint, sockets/bits: hexagon socket wrench sizes 4 to 14 mm, hex bit (| Allen) 3 to | o 6 mm | |
| Slot-head screwdriver 0.5 x 4 - 0.6 x 4.5 - 0.8 x 5.5 | | | |
| Crosshead screwdriver PH 1 - PH 2 - PH 3 - PZ 1 - PZ 2 - PZ 3 TORX® screwdriver T 10 - T 15 - T 20 | | | 1/4 |
| 280 x 130 x 90 mm | 1 | 11 3104 | 11111 111 111 1111 11 11 11 11 11 11 11 |
| | | | G |
| Socket wrench set, 52 pieces | | | 000000000000000000000000000000000000000 |
| in a robust metal case, tools made of chrome vanadium steel, high-gloss polish | ed and chr | ome-plated. | |
| Contents: | | | 1/4 |
| 1/4" socket wrench system | | | • |
| One of each of the following: Hex sockets 4 - 4.5 - 5 - 6 - 7 - 8 - 9 - 10 - 11 - 13 mm | | | |
| Ratchet with plastic handle, reversible for clockwise/counterclockwise rotation | ı. with ball | stop and quick re | lease button |
| that prevents sockets from being released accidentally, with 36-step ratcheting | | | |
| 115 mm T-handle with sliding head | (1 0 | J , | |
| Extension 75 mm | | | |
| Cardan joint 35 mm | | | |
| Holder for ¹ /4" hex bits | | | |
| ¹ /2" socket wrench system | | | |
| One of each of the following: | | | |
| Hex sockets 10 - 11 - 12 - 13 - 14 - 15 - 17 - 19 - 22 - 24 - 27 - 30 - 32 mm | | | |
| Hex socket 21 mm, with rubber clamp (spark plug wrench) | | | OPP OF F |
| Ratchet with plastic handle, reversible for clockwise/counterclockwise rotation | ı, with ball | stop and quick re | elease button |
| that prevents sockets from being released accidentally, with 36-step ratcheting | (pivoting a | angle 10°) | C C |
| 295 mm T-handle with sliding head | | | |
| Extensions 125 and 250 mm | | | |
| Cardan joint 65 mm | | | |
| | | | 14 |
| Scrow bit system 1/4" how drive | | | ~ |
| | | | |
| One of each of the following: | position. 1 | 180 mm | |
| One of each of the following: Ratchet screwdriver, clockwise/counterclockwise rotation or locking in middle | e position, ´ | 180 mm | |
| One of each of the following: Ratchet screwdriver, clockwise/counterclockwise rotation or locking in middle Standard bits in plastic holders: | position, ´ | 180 mm | |
| Screw bit system ¹ /4" hex drive One of each of the following: Ratchet screwdriver, clockwise/counterclockwise rotation or locking in middle Standard bits in plastic holders: Slot-head screwdriver 0.5 x 4 mm, 0.8 x 5.5 mm, 1.2 x 7 mm Cross-head screwdriver PH 1, PH 2, PH 3 | e position, ´ | 180 mm | |
| One of each of the following: Ratchet screwdriver, clockwise/counterclockwise rotation or locking in middle Standard bits in plastic holders: Slot-head screwdriver 0.5 x 4 mm, 0.8 x 5.5 mm, 1.2 x 7 mm Cross-head screwdriver PH 1, PH 2, PH 3 Hex socket screw key (Allen) 3 - 4 - 5 - 6 - 7 - 8 mm | e position, ´ | 180 mm | |
| One of each of the following: Ratchet screwdriver, clockwise/counterclockwise rotation or locking in middle Standard bits in plastic holders: Slot-head screwdriver 0.5 x 4 mm, 0.8 x 5.5 mm, 1.2 x 7 mm Cross-head screwdriver PH 1, PH 2, PH 3 | e position, ´ | 180 mm | |

11 3152

Article no.

1

PU

PU

Blade size (W x H x L mm)

Article no.

Advice and ordering: Phone: +49 (0)2191 3718-01, Fax: +49 (0)2191 3718-85, E-mail: order@cimco.de

Total length mm

Blade size (W x H x L mm)

69

cimco°