

## Data sheet

Commercial Art.No.: R1.611.1350.0

light curtain SLC4-SM14-1350

Safety Light Curtain Standard Muting, Transmitter + Receiver, Type 4, PL e, Resolution 14 mm (Finger Protection), Protective Field Height 1350 mm, Supply Voltage 24 V, Male Connector M12, Transmitter 5-poles, Receiver 8-poles, Female Connector M12, Transmitter 5-poles, Receiver 5-poles, Muting Function, Mounting L-Bracket Set included



certificates / approvals



## Technical data

### function

sensor element	Transmitter and receiver
with muting function	yes
with muting display	yes
with beam coding	yes
automatic start	yes
restart interlock	yes
alignment aid	yes
blinking	no
cascadable	yes

### technical data

type acc. EN 61496-1	4
resolution	14 mm
distance	0,2 - 10 m
connection	connector M12
nominal voltage	24 V
voltage type	DC
number of OSSD outputs	2
max. output current	250 mA
degree of protection (IP)	IP65/IP67
mission time TM	20 a
ambient temperature min.	-30 °C
ambient temperature max.	55 °C
housing material	aluminum

### safety parameters

category (ISO 13849-1)	4
PL (ISO 13849-1)	level e
SIL <sub>CL</sub> (IEC 62061)	3

PFH <sub>d</sub> (High demand mode)	2.62 E-8 1/h
HFT	1
SSF	100 %
DC	99 %
MTTF <sub>d</sub>	43 a
T <sub>M</sub>	20 a

**classification**

ECLASS 11	
ECLASS 8.1	27270910
ETIM 9.0	EC002549
ETIM 8.0	EC002549