



Crimp Lugs (Copper)

Standard crimp Lug that has been used in all sectors of the electrical industry and are know for there reliability. Crimping can be achieved with standard tools and dies

- » 99.9% Oxygen-free high conductivity Copper
- » Electro tinned
- » Inspection hole in lug to ensure conductor inserted properly

Part No. (mm)	Cable Size	Stud Size (mm)	Dimensions (mm)				
			A	B	C	D	E
Available on Request	1.5mm ²	4	18.5	8	1	9	7.5
Available on Request	1.5mm ²	5	18.5	8	1	9	7.5
Available on Request	1.5mm ²	6	19.5	10	0.8	10	7.5
ECS-LUG-S-2.5-4	2.5mm ²	4	19	8	1	9	8
ECS-LUG-S-2.5-5	2.5mm ²	5	20	10	0.8	11	8
ECS-LUG-S-2.5-6	2.5mm ²	6	20	10	0.8	11	8
Available on Request	2.5mm ²	8	26	11	0.7	15	8
ECS-LUG-S-4-5	4mm ²	5	22	10	1	11	9
ECS-LUG-S-4-6	4mm ²	6	22	10	1	11	9
Available on Request	4mm ²	8	26	12	0.8	15	9
Available on Request	4mm ²	10	32	15	0.8	19	9
ECS-LUG-S-6-5	6mm ²	5	23	10	1.2	11	10
ECS-LUG-S-6-6	6mm ²	6	27	12	1	15	10
ECS-LUG-S-6-8	6mm ²	8	27	12	1	15	10
Available on Request	6mm ²	10	32	15	0.8	19	10
ECS-LUG-S-10-5	10mm ²	5	27	12	1.8	13	10
ECS-LUG-S-10-6	10mm ²	6	27	12	1.8	13	10
ECS-LUG-S-10-8	10mm ²	8	29	14	1.6	15	10
ECS-LUG-S-10-10	10mm ²	10	32	15	1.5	18	10
Available on Request	10mm ²	12	38	18	1	22	10
ECS-LUG-S-16-6	16mm ²	6	39	11	2.4	16	19
ECS-LUG-S-16-8	16mm ²	8	39	14	1.7	16	19
ECS-LUG-S-16-10	16mm ²	10	41	16	1.5	18	19
ECS-LUG-S-16-12	16mm ²	12	46	18	1.2	23	19
ECS-LUG-S-25-6	25mm ²	6	41	13.5	2.4	16	21
ECS-LUG-S-25-8	25mm ²	8	41	13.5	2.4	16	21
ECS-LUG-S-25-10	25mm ²	10	44	16	1.9	19	21
Available on Request	25mm ²	12	48	18	1.6	23	21
ECS-LUG-S-35-6	35mm ²	6	45	16	3	19	21
ECS-LUG-S-35-8	35mm ²	8	45	16	3	19	21
ECS-LUG-S-35-10	35mm ²	10	45	18	2.6	19	21
ECS-LUG-S-35-12	35mm ²	12	51	20	2.2	24	22
Available on Request	35mm ²	16	61	22	2.2	32	23
Available on Request	50mm ²	6	46	18	3.3	18	22
ECS-LUG-S-50-8	50mm ²	8	46	18	3.3	18	22
ECS-LUG-S-50-10	50mm ²	10	46	18	3.3	18	22
ECS-LUG-S-50-12	50mm ²	12	52	21	2.7	24	22
Available on Request	50mm ²	16	58	23	2.7	30	22
Available on Request	70mm ²	6	54	21	3.5	24	24
ECS-LUG-S-70-8	70mm ²	8	54	21	3.5	24	24
ECS-LUG-S-70-10	70mm ²	10	54	21	3.5	24	24
ECS-LUG-S-70-12	70mm ²	12	54	21	3.5	24	24
Available on Request	70mm ²	16	61	26	3	30	24
Available on Request	95mm ²	6	60	25	4	26	27
ECS-LUG-S-95-8	95mm ²	8	60	25	4	26	27
ECS-LUG-S-95-10	95mm ²	10	60	25	4	26	27
ECS-LUG-S-95-12	95mm ²	12	60	25	4	26	27
Available on Request	95mm ²	16	61	28	3.5	30	27
Available on Request	120mm ²	8	64	30	5	26	30
ECS-LUG-S-120-10	120mm ²	10	64	30	5	26	30
ECS-LUG-S-120-12	120mm ²	12	64	30	5	26	30
Available on Request	120mm ²	16	72	30	5	32	30
Available on Request	150mm ²	6	71	32	5.8	32	30
ECS-LUG-S-150-8	150mm ²	8	71	32	5.8	32	30
ECS-LUG-S-150-10	150mm ²	10	71	32	5.8	32	30
ECS-LUG-S-150-12	150mm ²	12	75	32	5.8	36	30

Part No. (mm)	Cable Size	Stud Size (mm)	Dimensions (mm)				
			A	B	C	D	E
Available on Request	150mm ²	16	75	32	5.8	36	30
ECS-LUG-S-150-B	150mm ²	blank	75	32	5.8	36	30
Available on Request	185mm ²	8	74	36	5.8	32	32
ECS-LUG-S-185-10	185mm ²	10	74	36	5.8	32	32
ECS-LUG-S-185-12	185mm ²	12	79	36	5.8	36	32
Available on Request	185mm ²	16	79	36	5.8	36	32
ECS-LUG-S-185-B	185mm ²	blank	79	38	5.8	41	32
ECS-LUG-S-240-10	240mm ²	10	92	41	7	42	38
ECS-LUG-S-240-12	240mm ²	12	92	41	7	42	38
Available on Request	240mm ²	16	92	41	7	42	38
ECS-LUG-S-240-B	240mm ²	blank	92	41	7	42	38
ECS-LUG-S-300-10	300mm ²	10	101	46	7.8	46	42
ECS-LUG-S-300-12	300mm ²	12	101	46	7.8	46	42
ECS-LUG-S-300-16	300mm ²	16	101	46	7.8	46	42
Available on Request	300mm ²	20	101	46	7.8	46	42
ECS-LUG-S-300-B	300mm ²	blank	101	46	7.8	46	42
Available on Request	400mm ²	10	107	50	8	48	44
Available on Request	400mm ²	12	107	50	8	48	44
Available on Request	400mm ²	16	107	50	8	48	44
Available on Request	400mm ²	20	107	50	8	48	44
Available on Request	400mm ²	blank	107	50	8	48	44
Available on Request	500mm ²	10	119	56	9	55	50
Available on Request	500mm ²	12	119	56	9	55	50
Available on Request	500mm ²	16	119	56	9	55	50
Available on Request	500mm ²	20	119	56	9	55	50
Available on Request	500mm ²	blank	119	56	9	55	50
Available on Request	630mm ²	12	139	64.4	11	64	58
Available on Request	630mm ²	16	139	64.4	11	64	58
Available on Request	630mm ²	20	139	64.4	11	64	58
Available on Request	630mm ²	blank	139	64.4	11	64	58