

ETHERLINE RJ45 Connectors

FOR ETHERNET NETWORKS IN FACTORY INSTALLATIONS



ECS-P129 - UNSHIELDED

Features

Un Shielded
Standard RJ45 crimp tool required
4 Pair / Cat5e
7 Stranded: 26 to 24AWG



ECS-P129S - SHIELDED

Features

Shielded
Standard RJ45 crimp tool required
4 Pair / Cat5e
7 Stranded: 26 to 24AWG



SNAG COVERS

Features

For use with ECS-P129 and ECS-P129s connectors
Cable OD: 5-6mm
Available in Green, Blue, White, Black and Red



21700540 - FIELD MOUNTABLE

Features

Quick Termination / No Tools Required
4 Pair: Standard T568A
Suitable for speeds up to CAT5e
Solid Wire: 26 to 23AWG
7 Stranded: 26 to 24AWG



21700600 - FIELD MOUNTABLE

Features

Quick Termination / No Tools Required
4 Pair: Standard T568A
Solid Wire: 24 to 22AWG
7 Stranded: 27 to 22AWG
Cable OD: 5-9mm



21700605 - PROFINET COLOUR CODING

Features

Quick Termination / No Tools Required
2 Pair: ProfiNet YE, OG, BU, WH
Solid Wire: 24 to 22AWG
7 Stranded: 27 to 22AWG
Cable OD: 5-9mm



21700615 - FOR FD CABLES

Features

Quick Termination / No Tools Required
4 Pair: Standard T568A
For FD Dragchain Cables
Solid Wire: 26 to 24AWG
7 Stranded: 27 to 24AWG
19 Stranded: 26AWG
Cable OD: 5-9mm



ECS-P129S-JOINER

Features

For Joining Ethernet Patch Cables
Suitable for speeds up to CAT6A



21700639 - FOR FD CABLES

Features

Quick Termination / No Tools Required
4 Pair: Standard T568A
90 Degree cable exit
4 Way Mountable
For FD Dragchain Cables
Solid Wire: 26 to 24AWG
7 Stranded: 27 to 24AWG
19 Stranded: 26AWG
Cable OD: 5-10mm



21700636 - FOR STANDARD CABLES

Features

Quick Termination / No Tools Required
4 Pair: Standard T568A
90 Degree cable exit
4 Way Mountable
Solid Wire: 24 to 22AWG
7 Stranded: 27 to 22AWG
Cable OD: 5-10mm

