# **Fuse Holder Inserts, Bases & Plates**

## FOR ISOLATION AND PROTECTION OF CIRCUITS



#### Description

Fuse terminals with rocking head for disconnection. Takes standard 5x20mm glass fuses. 6.3mm x 32mm also on request.

#### Conductor Sizes


 Stranded: 0.13mm<sup>2</sup> to 4mm<sup>2</sup> • Solid: 0.13mm² to 6mm² Available in both Spring Clamp and Screw terminal options.

#### Features

Fuse insert can be pulled out and removed making it easy to check fuses

#### **Current Rating**

• Dependant on fuse



| Part No.           | Туре                    | Series          | Clamp  |  |  |  |
|--------------------|-------------------------|-----------------|--------|--|--|--|
| Bases              |                         |                 |        |  |  |  |
| 56.704.4055.0      | Fuse Terminal Base      | WKFN 4 TKG/35   | Spring |  |  |  |
| 57.504.4055.0      | Fuse Terminal Base      | WK 4 TKG/U /V0  | Screw  |  |  |  |
| End Plates         |                         |                 |        |  |  |  |
| 07.312.9055.0      | Grey End Plate          | APFN 4 D2/2     | Spring |  |  |  |
| 07.311.6155.0      | Grey End Plate          | AP 4 TK /V0     | Screw  |  |  |  |
| Inserts (5 x 20mm) |                         |                 |        |  |  |  |
| Z1.298.1053.0      | No LED Indication       | THSI 5X20       |        |  |  |  |
| Z1.298.1153.0      | 12-24V LED Indication   | THSI 5X20LED 24 |        |  |  |  |
| Z1.298.1253.0      | 24-60V LED Indication   | THSI 5X20LED 60 |        |  |  |  |
| Z1.298.1353.0      | 110-250V LED Indication | THSI 5X20GL 250 |        |  |  |  |

# **Fuse Holder Terminals**

#### FOR ISOLATION AND PROTECTION OF CIRCUITS

# wieland

#### Description

Fuse terminal block for standard glass fuses. Takes standard 5x20mm or 6.3x32mm glass fuses. Available in Screw Terminal only.



- Stranded: 0.13mm² to 4mm²
- Solid: 0.13mm² to 6mm²

Fully enclosed so it does not require an extra end plate. As it is all one piece, this makes it the most strong and robust fuse holder in the range.

#### **Current Rating**

• Dependant on fuse

| Part No.  | Type               | Series                 | Clamp |  |  |
|---|--------------------|------------------------|-------|--|--|
| for (5 $	imes$ 20mm, 5 $	imes$ 25mm and 5 $	imes$ 30mm) |                    |                        |       |  |  |
| 57.904.5355.0   | No LED Indication  | WK 4 / THSI5 U/V0      | Screw |  |  |
| 57.904.5555.0   | 24V LED Indication | WK 4/THSI5 LED 24U /V0 | Screw |  |  |
| Z7.255.8627.0   | Cross connector    | WKN 6 TK-6             |       |  |  |
| for (6.3 x 32mm)  |                    |                        |       |  |  |
| 57.904.6355.0   | No LED Indication  | WK 4/THSI6,3 U /V0     | Screw |  |  |

# **Automotive Fuse Terminals**

## FOR ISOLATION AND PROTECTION OF CIRCUITS



# wieland

## Description

Fuse terminal block for automotive fuses. This block takes the larger style ATO type automotive fuse.



## **Conductor Sizes**

- Stranded: 0.13mm² to 4mm²
- Solid: 0.13mm<sup>2</sup> to 6mm<sup>2</sup> Available in Spring Clamp only

## Features

· LED indication which is very useful when fault finding.

## **Current Rating**

• Dependant on fuse

| Part No.      | Туре                 | Series            | Clamp  |  |  |
|---------------|----------------------|-------------------|--------|--|--|
| Terminal      |                      |                   |        |  |  |
| 56.704.4155.0 | No LED Indication    | WKFN 4 FSI        | Spring |  |  |
| 56.704.4255.0 | 12Vdc LED Indication | WKFN 4 FSI LED 12 | Spring |  |  |
| 56.704.5355.0 | 24Vdc LED Indication | WKFN 4 FSI LED 24 | Spring |  |  |
| End Plate     |                      |                   |        |  |  |
| 07.312.9055.0 | Grey End Plate       | APFN 4 D2/2       | Spring |  |  |

# Resettable Blade Fuse MINIATURE CIRCUIT BREAKER



Miniature circuit breaker that fits into a standard automotive blade fuse holder. These units can be manually turned off and on via the button located at the top. The have built in over current protection.



| Part No.     | Current Rating | Voltage    | Height |  |  |
|--------------|----------------|------------|--------|--|--|
| BLADE MCB    |                |            |        |  |  |
| 1180-01-2.5A | 2.5A           | Up to 250V | 55mm   |  |  |
| 1180-01-4A   | 4A             | Up to 250V | 55mm   |  |  |
|              |                |            |        |  |  |

