

Product information Field Attachable M12 Connectors - Standard Type - RKC 4/9

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M12 Connectors: M12 Circular connector acc. to IEC 61076-2-101: M12 Field Attachable Connectors: Field Attachable M12

Connectors - Standard Type

 $https://www.e-catalog.beldensolutions.com: 443/link/57078-24228-256281-256292-256304-58429-58478-58928/en/RKCG_4-9/uistate$

Name	Field Attachable M12 Connectors - Standard Type



	Field attachable connector M10 famale connector straight varion with threeded joint accombling with corey terminals
Delivery informations	Field attachable connector, M12 female connector, straight version, with threaded joint, assembling with screw terminals
Availability	available
Product description	available
Type	RKC 4/9
Order No.	11215
Description	
•	Field attachable connector, M12 female connector, straight version, with threaded joint, assembling with screw terminals 4
Number of contacts	
Color of housing	black
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	straight
LED display present	×
Connectable conductor cross-section multiple wire	max. 0.75 mm ²
(without sleeve)	
Screw joint for cable for external cable diameter	4.0 mm 8.0 mm
Screwed cable gland, connecting thread	SW 19
Environmental conditions	
Environmental temperature	-25 °C 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-coppered, CuSnZn
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current In	4 A at 40°C, UL and notice derating
Nominal voltage	240 V
Rated voltage (Value)	250 V
Test voltage	2.0 kV eff./60 s
Insulation resistance	>1 6Ω
Approvals	
Approvals	UL
	I .





Belden Deutschland GmbH

Im Gewerbepark 2 58579 Schalksmühle Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

