3805392

PRODUCT DATA SHEET

Valid from: 04.SEP.2024

LAPP Cu/X-HF-90/HFS-90-TP 0.6/1kV BK



https://lappapac.lappgroup.com

1. Type

Cu/X-HF-90/HFS-90-TP 0.6/1kV

2. Application

AS/NZS 5000.1 standard cables are used for mains, submains and subcircuit power distribution including those enclosed in conduit, buried direct or in underground ducts for buildings and industrial plants where not subject to mechanical damage. Also available with reduced Earth core.

3. Reference Standard

3.1. AS/NZS 5000.1

4. Cable Construction

4.1. Conductor : Fine wire strands of bare copper wire acc. to AS/NZS 1125 Class 5

4.2. Core Insulation : Halogen free compound X-HF-90 acc. to AZ/NZS 3808

4.3. Core Identification : 3 Core – Red, Black, GN/YE

4 Core - Red, White, Blue GN/YE

5 Core - Red, White, Blue, Black, GN/YE

4.4. Binder Tape : Suitable tape wherever necessary

4.5. Sheath : Halogen free compound HFS-90-TP acc. to AZ/NZS 3808

4.6. Sheath Colour : Black, Similar RAL 9005

5. Technical Data

5.1. Rated Voltage U₀/U : 0.6/1kV

5.2. Test Voltage : Core/Core: 3500 V AC5.3. Min. Bending Radius : Fixed installation: 4 x D

5.4. Temperature Range : Fixed installation: -25°C to +90°C

5.5. Flammability : acc. to AS/NZS 1660.5.6
 5.6. Smoke Density : acc. to AS/NZS 1660.5.2
 5.7. Halogen Free : acc. to AS/NZS 1660.5.4
 5.8. UV-resistance : acc. to ISO 4892-2 method A

6. Identification

 $\text{U278} \leftarrow 5 \rightarrow \text{LAPP}^{\$} \text{ Cu/X-HF-90/HFS-90-TP ELECTRIC CABLE 0.6/1 kV FIXED APPLICATIONS ONLY} \leftarrow 5 \rightarrow \textbf{D} \leftarrow 5 \rightarrow \textbf{C} \leftarrow 5 \rightarrow \textbf{$

←10→ Artnr. Year/Week MM

Marking (Drucktext):

® Can be indicated as a symbolical point or symbolical circle if the font size is too small

Artnr. Part Number

D Dimension (e.g. 3 G 1.5 or 4 x 2 x 0.34)

←10→ Distance at least 10 mm (the blue arrow with the 10-mm-indication is not to be printed)
 ←5→ Distance at least 5 mm (the blue arrow with the 5-mm-indication is not to be printed)

Additional printing:

Each additional defined printing consists of:

MM Length marking (0000)

Colour of marking White

Elaborated by: LIZH5 / SVM	Document: SDB_3805392_EN Version: 04	Page 1 of 3
----------------------------	---	-------------

3805392

PRODUCT DATA SHEET

Valid from: 04.SEP.2024

LAPP Cu/X-HF-90/HFS-90-TP 0.6/1kV BK



https://lappapac.lappgroup.com

7. General Requirements

PWIS: All materials used for the cable during manufacturing shall be free of Paint-Wetting Impairment Substances, e.g. silicone.

RoHS: All homogeneous materials of all articles must not contain the substances of Annex II of the European Directive 2011/65/EU (RoHS) in excess of the concentration limits listed therein. Exemptions are allowable for the applications listed in Annex III and IV of the same Directive.

REACH: All materials used in the manufacturing process of the product are subject to the EC Regulation No. 1907/2006 regarding Registration, Evaluation, Authorization and Restriction of Chemicals (REACH). If substances based on the current Candidate List are used, they shall be listed with their designation and their concentration.

8. Tests

acc. to AS/NZS 5000.1

9. Dimensional Data

Article Number	No. of core(s) and conductor cross-section	Approx. Outer Diameter	Approx. Cable Weight
7 (Tuolo 14dilibol	mm ²	mm	Kg/Km
3805392	3 G 1.5	10.5	149
3805393	4 G 1.5	11.2	176
3805423	5 G 1.5	12.1	205
3805394	3 G 2.5	11.3	190
3805395	4 G 2.5	12.2	228
3805396	5 G 2.5	13.1	268
3805397	3 G 4	12.7	256
3805398	4 G 4	13.8	311
3805399	5 G 4	14.9	369
3805400	3 G 6	13.9	335
3805401	4 G 6	15.1	411
3805402	5 G 6	16.4	500
3805403	3 G 10	16.1	486
3805404	4 G 10	17.5	603
3805405	5 G 10	19.1	736
3805406	3 G 16	18.2	688
3805407	4 G 16	20.0	863
3805408	5 G 16	21.8	1058
3805409	4 G 25	24.7	1344
3805410	5 G 25	27.2	1654
3805411	4 G 35	28.2	1843
3805412	5 G 35	31.1	2271
3805413	4 G 50	33.9	2652
3805414	5 G 50	37.5	3288
3805415	4 G 70	39.3	3610
3805416	5 G 70	43.9	4513
3805417	4 G 95	44.9	4637
3805418	5 G 95	49.4	5710

Elaborated by: LIZH5 / SVM	Document: SDB_3805392_EN Version: 04	Page 2 of 3
----------------------------	---	-------------

3805392

PRODUCT DATA SHEET

Valid from: 04.SEP.2024

LAPP Cu/X-HF-90/HFS-90-TP 0.6/1kV BK



https://lappapac.lappgroup.com

10. Product Label

- 10.1. Every packaging unit shall have the following information indicated on the product label:
 - 10.1.1. Cable Standard Number
 - 10.1.2. Voltage Rating
 - 10.1.3. Number of Cores and Size of Conductor
 - 10.1.4. Designation of Insulation and Outer Sheath
 - 10.1.5. Article Number
 - 10.1.6. Length of Cable
 - 10.1.7. PO Number

10.2. Sample Product Label

Standard Label



www.lappgroup.com

U.I.Lapp GmbH Schulze-Delitzsch-Strasse 25 D – 70565 Stuttgart

LAPP Cu/X-HF-90/HFS-90-TP 0.6/1kV BK

Insulation / Outer Sheath: HFS-90-TP

Standard: AS/NZS 5000.1

Article: 3805392 PO No.: 45XXXXXXXX

Quantity: $M < m \rightarrow m >$

Elaborated by: LIZH5 / SVM Document: SDB_3805392_EN Version: 04 Page 3 of 3