

## Data Sheet | Item Number: 790-145

Carrier rail; with special perforations; 1000 mm long; tin-plated; silver-colored

<https://www.wago.com/790-145>



Color: ■ silver-colored

### Physical data

Width	1000 mm / 39.37 inches
-------	------------------------

### Material data

Color	silver-colored
Fire load	0 MJ
Weight	256 g

### Commercial data

eCl@ss 10.0	27-40-06-02
eCl@ss 9.0	27-40-06-02
ETIM 8.0	EC001285
ETIM 7.0	EC001285
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	IT
GTIN	4045454701109
Customs tariff number	72169180000

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Downloads

### Environmental Product Compliance

#### Compliance Search

Environmental Product Compliance 790-145



## Documentation

### Bid Text

790-145	19.02.2019	xml 2.53 KB	
790-145	31.08.2017	doc 23.00 KB	

## CAD/CAE-Data

### CAD data

2D/3D Models 790-145



### CAE data

EPLAN Data Portal 790-145



WSCAD Universe 790-145



ZUKEN Portal 790-145



## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Shield termination


##### 1.1.1.1 Shield termination




#### Item No.: 790-144

Stand off; for carrier rail; suitable for M5 size screw; with special perforations

## Installation Notes



Securing a spacer sleeve to a specialty slotted DIN-rail.



Securing an additional shield clamping saddle.

Tightening/removing a shield clamping saddle.

After connection, tighten the knurled screw to complete the installation.  
Recommended tightening torque: 0.5 Nm

To remove the clamping saddle, unscrew until ratcheted mechanism is released, then slightly tip saddle and remove the clamping saddle.