



Color: ■ yellow

Similar to illustration

### Technical data

Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	3,000 labels/reel; 2 lines
Printing device	Smart Printer (thermal transfer printer)

### Physical data

Depth	0.06 mm
Marking surface	6 x 15 mm

### Mechanical data

Mounting type	Sticking
Smear resistance	in conjunction with 258-5005 Ink Ribbon

### Material data

Color	yellow
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	Acrylic; permanent
Halogen-free	Yes
Weight	99.4 g
Fire load	0 MJ

### Environmental requirements

Ambient temperature (storage)	+10 ... +21 °C
Ambient temperature (operation)	-40 ... +150 °C
Relative humidity	40 ... 50 %

### Commercial data

eCl@ss 10.0	27-40-06-29
eCl@ss 9.0	27-40-06-29
ETIM 9.0	EC001288
ETIM 8.0	EC001288
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821632672
Customs tariff number	39199080888

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance  
210-805/000-002



### Documentation

#### Operating Instructions

210-805 Information on  
handling print material 1 28.08.2020 pdf  
1338.18 KB



### 1 Compatible Products

#### 1.1 Optional Accessories

##### 1.1.1 Marking

##### 1.1.1.1 Marking device



##### Item No.: 258-5000

Thermal transfer printer; Smart Printer; for  
complete control cabinet marking; 300  
dpi; With marking material