Data Sheet | Item Number: 282-885

Locking cover; mechanically locks multiple links; 5-pole; transparent

https://www.wago.com/282-885





 ${\sf Color:} \ \square \ {\sf transparent}$

Similar to illustration

Physical data

Width 39.2 mm / 1.543 inches

| Material data | |
|------------------------------------|---|
| Note (material data) | |
| | <u>Information on material specifications can be found here</u> |
| Color | transparent |
| Material group | Illa |
| Insulation material (main housing) | Polycarbonate (PC) |
| Flammability class per UL94 | V2 |
| Fire load | 0.12 MJ |
| Weight | 2.8 g |

| Environmental requirements | |
|----------------------------------|-------------|
| Processing temperature | -35 +85 ℃ |
| Continuous operating temperature | -60 +105 °C |

| Commercial data | |
|-----------------------|----------------------------------|
| Product Group | 1 (Rail Mounted Terminal Blocks) |
| eCl@ss 10.0 | 27-14-11-92 |
| eCl@ss 9.0 | 27-14-11-92 |
| ETIM 9.0 | EC002848 |
| ETIM 8.0 | EC002848 |
| PU (SPU) | 50 (10) pcs |
| Packaging type | Вох |
| Country of origin | DE |
| GTIN | 4045454636272 |
| Customs tariff number | 39269097900 |

Data Sheet | Item Number: 282-885

https://www.wago.com/282-885



Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 282-885



Documentation

| Additional Information | | |
|------------------------|-------------------|--------------------------|
| Technical Section | pdf 2246.92 KB | $\underline{\downarrow}$ |

| Bid Text | | | |
|----------|------------|-----------------|--------------------------|
| 282-885 | 19.02.2019 | xml 2.57 KB | \downarrow |
| 282-885 | 03.03.2017 | doc 23.50 KB | $\underline{\downarrow}$ |

CAD/CAE-Data

CAD data

2D/3D Models 282-885



CAE data

WSCAD Universe 282-885

Installation Notes

Locking system



Snapping transparent locking cover onto 1–8 disconnect links:

a) Mechanically lock several links for multi-pole switching applications b) Protect markers



Snapping transparent locking cover onto 1–8 disconnect links:

a) Mechanically lock several links for mul-

ti-pole switching applications

b) Protect markers

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at:: www.wago.com

Page 2/2 Version 20.11.2024