

## Data Sheet | Item Number: 282-384

Lock-out; for disconnect link; yellow

<https://www.wago.com/282-384>



Color: ■ yellow

### Material data

Note (material data)

[Information on material specifications can be found here](#)

Color	yellow
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.013 MJ
Weight	0.4 g

### Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

### Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
PU (SPU)	100 (20) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332283212
Customs tariff number	39269097900

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**

Compliance Search	
Environmental Product Compliance 282-384	↓

**Documentation**

Additional Information		
Technical Section	pdf 2246.92 KB	↓


Bid Text				
282-384	19.02.2019	xml 2.50 KB	↓	
282-384	03.03.2017	doc 23.00 KB	↓	

**CAD/CAE-Data**

CAD data	
2D/3D Models 282-384	↓

CAE data	
WSCAD Universe 282-384	↓
ZUKEN Portal 282-384	↓

**Installation Notes**



Lock-out snaps into one of two notched positions, preventing accidental operation of the disconnect link.