DB Distribution Box - split 360° cable entry system

for cables with and without connectors, M32 - M75* / IP54



With the new distribution box, centrally routed cables can be distributed 360° in all desired directions.


Cables (with and without connectors) with a diameter of 1 to 15 mm can be routed, sealed and strain relieved in accordance with EN 62444.

The distribution box is suitable for metric cut-outs M32 - M75* and can be fixed with a locknut, which is included in the delivery.

When using multi grommets, up to 48 cables can be routed and a high cable density is achieved.

Thanks to the screw mount cover and the use of split cable grommets, retrofits, repairs and maintenance can be done much more easily and quickly.

*M75 available from spring 2023



Specifications

IP rating (EN 60529)	IP54
Material	Polyamide
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, silicone free, halogen free
Mounting options	Fasten with locknut

Advantages & benefits

Fast and easy assembly

Easy distribution of cables in a 360° angle

Warranty on pre-terminated cables remains

Retrofits, repairs and maintenance can be done much more easily and quickly

Suitable for metric cut-outs M32 - M75*

Strain relief according to EN 62444

Use of the proven KT grommet system

High cable density, wide variety of grommets


High flexibility with the use of multi-range and IMAS-CONNECT™ adapter grommets

Hexagonal locknut included in the delivery

High stability, vibration resistant

Mechanical protection of the central entry point

Product types & sizes



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

Height 53 mm

Mounting height 39,4 mm


Cut-out size, metric M32

Thread M32 × 1,5

Thread length 13,6 mm

Suitable for grommets 3 x KT small

DB 3×2 | M50



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width


4251269332531 5 24 15 mm 94,5 mm 87 mm

54301

Height
Mounting height
Cut-out size, metric
Thread
Thread length
Suitable for grommets

53 mm 39,4 mm M50 M50 × 1,5 13,6 mm 6 x KT small

DB 3×3 | M63



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

