

KEL-DPZ multi-membrane cable entry plates, round

with metric threads M25 - M63 / IP66 / IP68 / UL Type 12/4X*



KEL-DPZ round cable entry plates are designed to route and seal cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The assembly of the KEL-DPZ round with unterminated cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ round provides strain relief and protection IP66 / IP68 / UL Type 4X*.

The round versions of the KEL-DPZ series have a thread to fit in metric cut-outs from M25 to M63. Thus cut-outs for metric cable glands can be used.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

*4X for indoor use only

IP54

IP55

IP64

IP65

IP66

IP67

IP68

UL TYPE
12

UL TYPE
4X

UL US

DNV

RIIR

HL3
EN 45545-2

EN 61373

ECOLAB
certified

UV
ISO 4892-2A

PNEUMATICS

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

Specifications


IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type (UL 50E)	UL Type 12, UL Type 4X*
Material	Elastomer Base frame: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Fasten with locknut

Advantages & benefits

- Fast mounting
- High cable density
- Certified protection IP66/IP68 (acc. to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric cut-outs
- Hexagonal locknut included in the delivery
- Hygienic design - free of dirt-collecting recesses


Product types & sizes

KEL-DPZ 25|3 gy



Part No. **43736**
EAN **4251269320439**
Package quantity **10**
For max. no. of cables **3**
Colour **grau (ähnlich RAL 7035)**
Height **22 mm**
External diameter **39 mm**

Mounting height **8 mm**
Cut-out size, round **25,3 mm**
Cut-out size, metric **M25**
Thread **M25 x 1,5**
Thread length **14 mm**
Clamping range **2 x 3.2 - 5.2 mm**
1 x 3.2 - 6.5 mm


KEL-DPZ 25|3 bk

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

50736
4251269320453
10
3
schwarz
22 mm
39 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
25,3 mm
M25
M25 × 1,5
14 mm
2 x 3.2 - 5.2 mm
1 x 3.2 - 6.5 mm


KEL-DPZ 25|4 gy

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

43737
4251269320446
10
4
grau (ähnlich RAL 7035)
22 mm
39 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
25,3 mm
M25
M25 × 1,5
14 mm
4 x 3.2 - 5.2 mm


KEL-DPZ 25|4 bk

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

50737
4251269320460
10
4
schwarz
22 mm
39 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
25,3 mm
M25
M25 × 1,5
14 mm
4 x 3.2 - 5.2 mm


KEL-DPZ 32|4 gy

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

43732
4251269310539
10
4
grau (ähnlich RAL 7035)
22 mm
44 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
32,3 mm
M32
M32 × 1,5
14 mm
3 x 3.2 - 6.5 mm
1 x 7.2 - 12.5 mm


KEL-DPZ 32|4 bk

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

50732
4251269315152
10
4
schwarz
22 mm
44 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
32,3 mm
M32
M32 × 1,5
14 mm
3 x 3.2 - 6.5 mm
1 x 7.2 - 12.5 mm


KEL-DPZ 32|4-2 gy

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

43733
4251269310546
10
4
grau (ähnlich RAL 7035)
22 mm
44 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
32,3 mm
M32
M32 × 1,5
14 mm
4 x 5 - 9.5 mm


KEL-DPZ 32|4-2 bk

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

50733
4251269315169
10
4
schwarz
22 mm
44 mm


Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
32,3 mm
M32
M32 × 1,5
14 mm
4 x 5 - 9.5 mm

KEL-DPZ 32|7 gy


Part No. **43734**
 EAN **4251269310553**
 Package quantity **10**
 For max. no. of cables **7**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 × 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ 32|7 bk


Part No. **50734**
 EAN **4251269315176**
 Package quantity **10**
 For max. no. of cables **7**
 Colour **schwarz**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 × 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ 40|8 gy


Part No. **43741**
 EAN **4251269310577**
 Package quantity **10**
 For max. no. of cables **8**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **52 mm**

Mounting height **8 mm**
 Cut-out size, round **40,4 mm**
 Cut-out size, metric **M40**
 Thread **M40 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ 40|8 bk


Part No. **50741**
 EAN **4251269315190**
 Package quantity **10**
 For max. no. of cables **8**
 Colour **schwarz**
 Height **22 mm**
 External diameter **52 mm**

Mounting height **8 mm**
 Cut-out size, round **40,4 mm**
 Cut-out size, metric **M40**
 Thread **M40 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ 50|8 gy


Part No. **43750**
 EAN **4251269310584**
 Package quantity **10**
 For max. no. of cables **8**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm


KEL-DPZ 50|8 bk

Part No. **50750**
 EAN **4251269315206**
 Package quantity **10**
 For max. no. of cables **8**
 Colour **schwarz**
 Height **22 mm**
 External diameter **62 mm**


Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm

KEL-DPZ 50|10 gy


Part No.	43751	Mounting height	8 mm
EAN	4251269310591	Cut-out size, round	50,4 mm
Package quantity	10	Cut-out size, metric	M50
For max. no. of cables	10	Thread	M50 × 1,5
Colour	grau (ähnlich RAL 7035)	Thread length	14 mm
Height	22 mm	Clamping range	7 x 3.2 - 6.5 mm
External diameter	62 mm		2 x 5 - 10.2 mm
			1 x 16 - 22.2 mm

KEL-DPZ 50|10 bk


Part No.	50751	Mounting height	8 mm
EAN	4251269315213	Cut-out size, round	50,4 mm
Package quantity	10	Cut-out size, metric	M50
For max. no. of cables	10	Thread	M50 × 1,5
Colour	schwarz	Thread length	14 mm
Height	22 mm	Clamping range	7 x 3.2 - 6.5 mm
External diameter	62 mm		2 x 5 - 10.2 mm
			1 x 16 - 22.2 mm

KEL-DPZ 50|12 gy


Part No.	43752	Mounting height	8 mm
EAN	4251269310607	Cut-out size, round	50,4 mm
Package quantity	10	Cut-out size, metric	M50
For max. no. of cables	12	Thread	M50 × 1,5
Colour	grau (ähnlich RAL 7035)	Thread length	14 mm
Height	22 mm	Clamping range	4 x 3.2 - 6.5 mm
External diameter	62 mm		8 x 5 - 10.2 mm

KEL-DPZ 50|12 bk


Part No.	50752	Mounting height	8 mm
EAN	4251269315220	Cut-out size, round	50,4 mm
Package quantity	10	Cut-out size, metric	M50
For max. no. of cables	12	Thread	M50 × 1,5
Colour	schwarz	Thread length	14 mm
Height	22 mm	Clamping range	4 x 3.2 - 6.5 mm
External diameter	62 mm		8 x 5 - 10.2 mm

KEL-DPZ 50|19 gy

Part No.	43758	Mounting height	8 mm
EAN	4251269310621	Cut-out size, round	50,4 mm
Package quantity	10	Cut-out size, metric	M50
For max. no. of cables	19	Thread	M50 × 1,5
Colour	grau (ähnlich RAL 7035)	Thread length	14 mm
Height	22 mm	Clamping range	19 x 3.2 - 6.5 mm
External diameter	62 mm		

KEL-DPZ 50|19 bk

Part No.	50758	Mounting height	8 mm
EAN	4251269315244	Cut-out size, round	50,4 mm
Package quantity	10	Cut-out size, metric	M50
For max. no. of cables	19	Thread	M50 × 1,5
Colour	schwarz	Thread length	14 mm
Height	22 mm	Clamping range	19 x 3.2 - 6.5 mm
External diameter	62 mm		


KEL-DPZ 50|78 gy

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

43756
4251269310614
10
78
grau (ähnlich RAL 7035)
22 mm
62 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
50,4 mm
M50
M50 × 1,5
14 mm
76 x 1.5 - 2.6 mm
2 x 2.5 - 5 mm


KEL-DPZ 50|78 bk

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

50756
4251269315237
10
78
schwarz
22 mm
62 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
50,4 mm
M50
M50 × 1,5
14 mm
76 x 1.5 - 2.6 mm
2 x 2.5 - 5 mm


KEL-DPZ 63|9 gy

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

43760
4251269310638
10
9
grau (ähnlich RAL 7035)
22 mm
75 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
63,4 mm
M63
M63 × 1,5
14 mm
1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|9 bk

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

50760
4251269315251
10
9
schwarz
22 mm
75 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
63,4 mm
M63
M63 × 1,5
14 mm
1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ 63|13 gy

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

43761
4251269310645
10
13
grau (ähnlich RAL 7035)
22 mm
75 mm

Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
63,4 mm
M63
M63 × 1,5
14 mm
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm


KEL-DPZ 63|13 bk

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Height
External diameter

50761
4251269315268
10
13
schwarz
22 mm
75 mm


Mounting height
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Clamping range

8 mm
63,4 mm
M63
M63 × 1,5
14 mm
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

KEL-DPZ 63|14 gy


Part No. **43762**
 EAN **4251269310652**
 Package quantity **10**
 For max. no. of cables **14**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **14 mm**
 Clamping range **14 x 5 - 10.2 mm**

KEL-DPZ 63|14 bk


Part No. **50762**
 EAN **4251269315275**
 Package quantity **10**
 For max. no. of cables **14**
 Colour **schwarz**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **14 mm**
 Clamping range **14 x 5 - 10.2 mm**

KEL-DPZ 63|35 gy

Part No. **43763**
 EAN **4251269310669**
 Package quantity **10**
 For max. no. of cables **35**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **14 mm**
 Clamping range **35 x 3.2 - 6.5 mm**

KEL-DPZ 63|35 bk

Part No. **50763**
 EAN **4251269315282**
 Package quantity **10**
 For max. no. of cables **35**
 Colour **schwarz**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **14 mm**
 Clamping range **35 x 3.2 - 6.5 mm**