LFZ|SKLEMC Shield clamps for screw assembly





	Туре	Order No.	Shield diameter	Fixing hole	PU	
Product description LFZ SKL shield clamps can be used for shielding single cables. The shield clamps are easy to use and enable a reliable shielding	LFZ SKL 1.5-3	36910	1.5 - 3 mm	4.2 mm	10	
of cables. Cables are secured with a cable tie. Strain relief in accordance with EN 50262 / 62444 is achieved.	LFZ SKL 3-6	36915	3 - 6 mm	4.2 mm	10	
LFZ SKL shield clamps are easily attached to mounting plates via screw.	LFZ SKL 6-8	36920	6 - 8 mm	4.2 mm	10	
Advantages Integrated strain relief Optimal contact of the cable shield Simple assembly	LFZ SKL 8-11	36925	8 - 11 mm	4.2 mm	10	
 Permanent and continuous pressure on the cable shield, no adjustment of the spring load required Vibration proof, maintenance free Specifications	LFZ SKL 12-16	36930	12 - 16 mm	4.2 mm	10	
Material SKL-clamp Spring steel, zinc plated LFZ-foot Sheet steel, galvanically zinc plated Fixing hole 4.2 mm for screw M4	LFZ SKL 17-22	36935	17 - 22 mm	4.2 mm	10	
Accessories KB Cable ties 159 Stripping tool 113	LFZ SKL 23-29	36940	23 - 29 mm	4.2 mm	10	