


CEE Plugs




Plug IP44 SHARK

| | 16 Amp | | | 32 Amp | | |
|---|--------|------|------|---------|---------|---------|
| | 3 | 4 | 5 | 3 | 4 | 5 |
| Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| a [mm] | 122 | 128 | 134 | 150 | 150 | 155 |
| b [mm] | 86 | 92 | 98 | 104 | 104 | 109 |
| c [mm] | 47 | 53 | 61 | 63 | 63 | 70 |
| K_cable Ø [mm] | 6-15 | 6-15 | 8-16 | 11,5-20 | 11,5-20 | 11,5-22 |
| Wire flexible [mm ²] | 1-2,5 | | | 2,5-6 | | |
| Contact screws [Ncm] | 100 | | | 110 | | |
| SW [mm] | 42 | 42 | 42 | 50 | 50 | 50 |
| Weight [g] | 109 | 128 | 151 | 181 | 201 | 232 |

- with screw terminals
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 015-6v

IP44 splashproof




Plug IP44 SHARK TT

| | 16 Amp | | | 32 Amp | | |
|---|--------|------|------|---------|---------|---------|
| | 3 | 4 | 5 | 3 | 4 | 5 |
| Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| a [mm] | 122 | 128 | 134 | 150 | 150 | 155 |
| b [mm] | 86 | 92 | 98 | 104 | 104 | 109 |
| c [mm] | 47 | 53 | 61 | 63 | 63 | 70 |
| K_cable Ø [mm] | 6-15 | 6-15 | 8-16 | 11,5-20 | 11,5-20 | 11,5-22 |
| Wire flexible [mm ²] | 1-2,5 | | | 2,5-6 | | |
| SW [mm] | 42 | 42 | 42 | 50 | 50 | 50 |
| Weight [g] | 111 | 132 | 156 | 186 | 206 | 241 |

- screwless connection technology
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 015-6TTv

IP44 splashproof




Plug IP67 SHARK

| | 16 Amp | | | 32 Amp | | |
|---|--------|------|------|---------|---------|---------|
| | 3 | 4 | 5 | 3 | 4 | 5 |
| Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| a [mm] | 122 | 128 | 134 | 150 | 150 | 155 |
| b [mm] | 71 | 79 | 87 | 93 | 93 | 100 |
| K_cable Ø [mm] | 6-15 | 6-15 | 8-16 | 11,5-20 | 11,5-20 | 11,5-22 |
| Wire flexible [mm ²] | 1-2,5 | | | 2,5-6 | | |
| Contact screws [Ncm] | 100 | | | 110 | | |
| SW [mm] | 42 | 42 | 42 | 50 | 50 | 50 |
| Weight [g] | 130 | 154 | 183 | 223 | 242 | 276 |

- with screw terminals
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 0152-6v

IP66/67 watertight



Plug IP67 SHARK TT

| | 16 Amp | | | 32 Amp | | |
|---|--------|------|------|---------|---------|---------|
| | 3 | 4 | 5 | 3 | 4 | 5 |
| Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| a [mm] | 122 | 128 | 134 | 150 | 150 | 155 |
| b [mm] | 71 | 79 | 87 | 93 | 93 | 100 |
| K_cable Ø [mm] | 6-15 | 6-15 | 8-16 | 11,5-20 | 11,5-20 | 11,5-22 |
| Wire flexible [mm ²] | 1-2,5 | | | 2,5-6 | | |
| SW [mm] | 42 | 42 | 42 | 50 | 50 | 50 |
| Weight [g] | 132 | 157 | 188 | 227 | 246 | 285 |

- screwless connection technology
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 0152-6TTv

IP66/67 watertight

