


CEE Connectors




Connector IP44

POWER TWIST

	63 Amp		
	3	4	5
Poles	3	4	5
a [mm]	269	269	269
b [mm]	107	107	107
K_cable Ø [mm]	14,5-36	14,5-36	14,5-36
Wire flexible [mm ²]	6-16		
Contact screws [Ncm]	200		
SW [mm]	61	61	61
Weight [g]	628	668	724

- contact frame with screws
- housing material: PA6
- contacts: brass with lamellar contact CuBe
 - **to order with pilot contact add a „5“** e.g. 23351-6 (see page 8)
 - to order with pilot contact system (PCS) please add a „6“ e.g. 23361-6 (see page 8)

IP44 splashproof




Connector IP66/67

POWER TWIST

	63 Amp		
	3	4	5
Poles	3	4	5
a [mm]	269	269	269
b [mm]	114	114	114
K_cable Ø [mm]	14,5-36	14,5-36	14,5-36
Wire flexible [mm ²]	6-16		
Contact screws [Ncm]	200		
SW [mm]	61	61	61
Weight [g]	673	714	772

- contact frame with screws
- housing material: PA6
- contacts: brass with lamellar contact CuBe
 - **to order with pilot contact add a „5“** e.g. 2335-6 (see page 8)
 - to order with pilot contact system (PCS) please add a „6“ e.g. 2336-6 (see page 8)

IP66/67 watertight



Connector IP66/67

POWER TWIST

	125 Amp		
	3	4	5
Poles	3	4	5
a [mm]	287	287	287
b [mm]	124	124	124
K_cable Ø [mm]	22,5-50	22,5-50	22,5-50
Wire flexible [mm ²]	16-50		
Contact screws [Ncm]	450		
SW [mm]	81	81	81
Weight [g]	1060	1167	1266

- contact frame with hexagon socket screws
- housing material: PA6
- contacts: brass with lamellar contact CuBe
 - **to order with pilot contact add a „5“** e.g. 2435-6 (see page 8)
 - to order with pilot contact system (PCS) please add a „6“ e.g. 2436-6 (see page 8)

IP66/67 watertight

**POWER
TWIST**



- ✓ Safety
- ✓ High impact resistance
- ✓ Optimum grip
- ✓ Large connection area
- ✓ Time saving

Amp.	Poles	pack. unit	110V~	230V~	400V~	500V~	>50-500V~	>50-500V~
			50/60Hz 4h	50/60Hz 3p=6h 4p+5p=9h	50/60Hz 3p=9h 4p+5p=6h	50/60Hz 7h	100-300Hz 10h	301-500Hz 2h
			Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.
63	3	2	2331-4	2331-6	2331-9	2331-7	2331-10	2331-2
63	4	2	2341-4	2341-9	2341-6	2341-7	2341-10	2341-2
63	5	2	2351-4	2351-9	2351-6	2351-7	2351-10	2351-2



2351-6

63	3	2	233-4	233-6	233-9	233-7	233-10	233-2
63	4	2	234-4	234-9	234-6	234-7	234-10	234-2
63	5	2	235-4	235-9	235-6	235-7	235-10	235-2



235-6

125	3	2	243-4	243-6	243-9	243-7	243-10	243-2
125	4	2	244-4	244-9	244-6	244-7	244-10	244-2
125	5	2	245-4	245-9	245-6	245-7	245-10	245-2



245-6

One contact
for extreme
environments

